

DULUX AcraTex 951 Coventry Coarse

PRODUCT CODE 194-85753

Data Sheet No. AUDA1065

APPROVALS

Description

DULUX AcraTex 951 Coventry Coarse is a decorative, low build protective coating displaying excellent resistance to weathering and atmospheric chemicals. The finish will resemble that of a coarse granular render which is sponge floated.

Features

Long 'wet edge' Standard Grade
 Faster Dry "Accent Base Winter Grade"
 Available in Standard, Accent & Extra Bright base's
 Even granular appearance

Benefits

Easy to apply
 Improved productivity in colder weather
 Extended Colour Range
 Tough



Uses

For interior/exterior application to both new and old masonry. DULUX AcraTex 951 Coventry Coarse is trowel applied and finished to achieve an even coarse granular appearance.

Performance Guide

Weather	Excellent resistance to cracking, flaking and chalking as part of a full system.	Salt	Resists salt spray especially when topcoated with DULUX AcraTex 955 AcraShield.
Heat	Up to 90C (dry)	Water	Water resistant with good vapour permeability.
Solvent	Resists alcohol and aliphatic hydrocarbons. Sensitive to strong solvents.	Abrasion	Good resistance to abrasion especially when topcoated with DULUX 955 AcraTex AcraShield .
Acid	Slight softening with dilute acid. Inert when topcoated with DULUX AcraTex 955 AcraShield.	Alkali	Slight softening with dilute alkali. Inert when topcoated with DULUX AcraTex 955 AcraShield

Typical Properties and Application Data

Gloss Level	Matt	Thinner	Not recommended
Gloss Level Ind		Spread Rate	0.8 sqm/L
Volume Solids	75.0	Components	1
Colour	Tint to White base colours, or factory tinted to order. Max 1y per litre tint.	Toxicity	Lead free. Forms a non-toxic film conforming to AS 1647, Part 3.
Number of Coats	1	Shelf life	24 months maximum
V.O.C Level	< 35 g/L untinted	Wet film per coat	Recommended 1333 µm
Touch Dry	60 minutes	Dry film per coat	Recommended 1000 µm
Application Method		Recoat	24 hours

DULUX AcraTex 951 Coventry Coarse

Data Sheet No.	AUDA1065
-----------------------	-----------------

Application Guide

Surface Preparation

Ensure alkaline surfaces have aged for 30 days minimum.

All surfaces must be thoroughly clean and free of all contaminants, dirt, surface chalk, grease, mould, mildew, wax, loose or flaky paint, form oils, release agents and mortar splashes. Metal, tie wire, etc. on surface must be removed or treated against corrosion. Surface imperfections and irregularities should be levelled and patched and completely flush to surrounding surfaces.

Maximum coverage and durability is assured by first using DULUX AcraTex 501 AcraPrime.

Application Procedure and Equipment

Product should be thoroughly mixed before use.

Refer to the DULUX AcraTex Application Manual for detailed application instructions.

Use masking to protect adjacent areas. The area should be patched and primed ready for final texture coat.

DULUX AcraTex 951 Coventry Coarse is applied by hawk and stainless steel trowel, then finished in a circular motion with the plastic finishing float to achieve an even granular appearance.

Two applicators are required for most areas - one applying the other processing the finish. Delivery must be to a uniform thickness. Allow the material to stand for a short time before "rubbing up" with float to produce the desired pattern/texture. Application must be in a brisk uniform fashion terminating when the whole area is complete, banded by a natural break such as an expansion joint, corner etc. Application commenced on a single area must be completed uninterrupted.

Trowel and Hawk finished with a plastic float

Health and Safety

MSDS Number 10965

Health Effects For detailed information refer to product label and the current Material Safety Data Sheet available through Dulux Sales and Customer Service offices 132377 AUS.
Health Effects: Splashes to the eye may cause eye irritation.
Personal Protective Equipment: Wear eye protection.

In the case of emergency please call 1800 033 111

Precautions and Limitations

A minimum spread rate of 0.8 square metres per litre is required.

Do not apply externally in temperatures below 10C or when the temperature of the surface may fall below 10C during the drying period.

When the weather is doubtful avoid application.

Must be protected from rain and frost for the first 24 hours.

Avoid application in hot, windy conditions or on hot surfaces.

To ensure colour uniformity and for optimum performance topcoat with DULUX AcraTex 955 AcraShield. Ensure that you have adequate tinted stock to complete the job in one application.

All material must be thoroughly cross-mix to ensure tint uniformity.

Check colour prior to application.

IMPORTANT: Not all colours are suitable for exterior use.

DULUX AcraTex 951 Coventry Coarse is not suitable for roller or spray applied finishes.

Transport and Storage

Pack A 194-85753

Sizes 15 Litre

Weight 23.5kg

Data Sheet	DULUX AcraTex 951 Coventry Coarse		
DuSpec Data Code	AUDA1065	Page No	2 of 3
Issue No	12.0	Date Issued	14/12/2011



DATA SHEET



DULUX AcraTex 951 Coventry Coarse

	Data Sheet No.	AUDA1065
--	-----------------------	-----------------

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "AcraTex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427

Data Sheet	DULUX AcraTex 951 Coventry Coarse		
DuSpec Data Code	AUDA1065	Page No	3 of 3
Issue No	12.0	Date Issued	14/12/2011