

DULUX AcraTex 951 Trowel On Tuscany Super Fine

PRODUCT CODE 194-85641

Data Sheet No. AUDA1068

APPROVALS

Description

DULUX AcraTex 951 Trowel On Tuscany Super Fine is a high build acrylic based coating, formulated on 100% pure acrylic emulsions, inert mineral fillers, graded aggregates, fungicides and colour stable pigments.

Features

7 year warranty
Water based
Fast processing
Long 'wet edge'

Benefits

Tough
Water resistant
Guaranteed long term exterior
Quick, efficient fine trowel render appearance

Uses

DULUX AcraTex 951 Trowel On Tuscany Super Fine can be applied to any sound masonry substrate, it has been carefully formulated to produce a tough, water resistant fine trowel rendered appearance. The cured coating has a mottled aged rendered patina and is similar to that of a sponge fine render. It is ideally suited for the renovation of heritage facades or for a traditional natural "render look" to a new structure of either contemporary or traditional architectural style. Technically, DULUX AcraTex 951 Trowel On Tuscany Super Fine delivers the charm of yester-year with the benefits of today's technology and unlike limewash or cement based coatings, it will not develop surface cracks and is virtually maintenance free.

Performance Guide

Weather	Excellent resistance to cracking, flaking and chalking as part of the full AcraTex system.	Salt	Resists salt spray
Heat	Up to 90C (dry film)	Water	Water Vapour Transmission 56.5 g/24hr/sq.m. Water Transmission 220g/24hr/sq.m/kPa.
Solvent	Resists alcohols & aliphatic hydrocarbons. Sensitive to other strong solvents.	Abrasion	Excellent resistance to abrasion.
Acid	Slight softening with dilute acids. Best when topcoated with DULUX AcraTex 955 AcraShield	Alkali	Slight softening with dilute alkalis. Best when topcoated with DULUX AcraTex 955 AcraShield

Data Sheet	DULUX AcraTex 951 Trowel On Tuscany Super Fine		
DuSpec Data Code	AUDA1068	Page No	1 of 3
Issue No	7.0	Date Issued	14/12/2011


DULUX AcraTex 951 Trowel On Tuscany Super Fine

Data Sheet No. AUDA1068

Typical Properties and Application Data

Gloss Level	Matt	Thinner	Not recommended.
Gloss Level Ind		Spread Rate	1.0 sqm/L
Volume Solids	75.0	Components	1
Colour	White & range of colours including exterior hues from the Dulux range. 1Y per litre maximum tint.	Toxicity	Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.
Number of Coats	One	Shelf life	24 months maximum
V.O.C Level	< 60 g/L untinted	Wet film per coat	Recommended 1000 µm
Touch Dry	60 minutes	Dry film per coat	Recommended 750 µm
Clean Up	Clean all equipment with water.	Recoat	24 hours

Application Method



Application Guide

Surface Preparation

Ensure all surfaces are clean, sound, free of dust, form oils, release agents and other foreign matter. Surfaces of powdery nature will require consolidation with DULUX AcraTex 501/2 Acra Prime as a sealer. Surface imperfections, misalignments and protrusions must be levelled and patched flush to the surrounding surfaces. Remove or treat against corrosion all metal objects on the surface. It is recommended that all surfaces be primed with DULUX AcraTex 501 Acra Prime to achieve even surface absorption prior to the application of DULUX AcraTex 951 Trowel On Tuscany Super Fine.

Application Procedure and Equipment

DULUX AcraTex 951 Trowel On Tuscany Super Fine is applied to the substrate via trowel and hawk at the minimum rate of 0.8 square metres per litre depending on the substrate condition and porosity. Once applied by stainless steel trowel the product is processed with a plastic finishing float to a uniform fine trowel finish. Single areas are completed in one application so as to avoid joint marks. Large areas will need to be articulated into workable sections especially during periods of high temperatures. Product should be thoroughly mixed before use.

Trowel and Hawk finished with a plastic trowel

Health and Safety

MSDS Number	10186	Using Safety Precautions	Wear eye protection and appropriate spray mask.
Health Effects	For detailed information refer to the product label or the current Material Safety Data Sheet available through Dulux Sales and Customer Service Offices 132377AUS. Health Effects: Splashes to the eye may cause irritation, mist inhalation may produce respiratory irritation.	Storage	0

In the case of emergency please call 1800 033 111

Data Sheet	DULUX AcraTex 951 Trowel On Tuscany Super Fine		
DuSpec Data Code	AUDA1068	Page No	2 of 3
Issue No	7.0	Date Issued	14/12/2011

Dulux**DuSpec****DATA SHEET****Dulux AcraTex****DULUX AcraTex 951 Trowel On Tuscany Super Fine**Data Sheet No. **AUDA1068****Precautions and Limitations**

A DULUX warranty will be provided confirming protection against flaking & peeling for a period of seven years when the full AcraTex system is applied by a Dulux trained applicator, according to specification, & at the specified spreading rates, & to the surface preparation details described in the AcraTex Specification Manual.

DULUX AcraTex 951 Trowel On Tuscany Super Fine must only be applied in air temperatures between 10C and 30C and must be protected from rain and frost for the first 24 hours. Avoid application in full sun or hot, windy conditions.

Transport and Storage

Pack A	194-85641	Flash point	NA
Sizes	15 Litre	UN Number	NA
Weight	23.5kg	Package Group	NA
Dangerous Goods Class	NA		
Shipment Name	Not dangerous goods. No special transport requirements.		

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "AcraTex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427

Data Sheet	DULUX AcraTex 951 Trowel On Tuscany Super Fine		
DuSpec Data Code	AUDA1068	Page No	3 of 3
Issue No	7.0	Date Issued	14/12/2011