

DULUX AcraTex 950 Roll On 00 Interior

PRODUCT CODE 194-20810

Data Sheet No. AUDA1410

APPROVALS

Description

DULUX AcraTex 950 Roll On 00 Interior texture coating is a non-granular, water based acrylic texture coatings for application to various interior substrates to provide a decorative high profile finish.

Features

Water based
Easy to texture
Versatile application

Benefits

Easy Application, safe and economical clean-up.
Range of texture profiles possible.
Quick, efficient application with roller, spray and brush.

Uses

Use DULUX AcraTex 950 Roll On 00 Interior textured coatings where a highly decorative stippled finish is required on suitably prepared internal surfaces. DULUX AcraTex 950 Roll On 00 Interior is a low profile, non granular coating. For optimum performance topcoat with DULUX premium Interior products.

Performance Guide

Weather	Designed for interior use only. Not recommended for exterior use	Heat	Up to 90C (dry).
Solvent	Resists alcohol and aliphatic hydrocarbons. Sensitive to strong solvents.	Abrasion	Good abrasion resistance especially when topcoated .
Alkali	Slight softening with dilute alkali.		

Typical Properties and Application Data

Gloss Level	Matt	Thinner	Not recommended
Gloss Level Ind		Spread Rate	1.5 sqm/L
Volume Solids	38.0	Components	1
Colour	White & stored tinted to pastel shades or factory tinted to order. Tint maximum 2Y per litre.	Toxicity	Lead free. Dry film is non-toxic and conforms to AS1647, Part 3 .
Number of Coats	One	Shelf life	24 months maximum.
V.O.C Level	< 50 g/L untinted	Wet film per coat	Recommended 684 µm
Touch Dry	60 Minutes	Dry film per coat	Recommended 260 µm
Clean Up	Clean all equipment with water after use.	Recoat	24Hours

Application Method


DULUX AcraTex 950 Roll On 00 Interior

Data Sheet No.	AUDA1410
-----------------------	-----------------

Application Guide

Surface Preparation

All surfaces must be cured, clean, sound and free of all contaminants such as forms oils, release agents & mortar splashes. Surface imperfections misalignments & protrusions must be levelled, patched & completely flush to surrounding surfaces. Metal, tie wire etc on surface must be removed or treated against corrosion. Apply DULUX premium primer, sealer or undercoat relevant to Dulux substrate guidelines. Ensure that it is cured completely and covers the substrate evenly.

Application Procedure and Equipment

Product should be thoroughly mixed before use.

Refer to the DULUX AcraTex Application Manual for detailed application instructions.

00 Interior Grade: Low profile by regular texture roller at 1.53 sq.m/l, high profile by coarse texture roller at 1.3sq.m/l, stucco by regular texture roller/steel trowel at 1.25 sq.m/l, stipple by spray - hopper gun at 1.7 sq.m/l.

Texture Roller or Hopper Gun

Health and Safety

MSDS Number 21853

Using Safety Precautions Wear eye protection

Health Effects For detailed information refer to current Material Safety Data Sheet available through Dulux Sales and Customer Service Offices 132377 AUS. Health Effects: Splashes to the eye may cause eye irritation.

Storage 0

In the case of emergency please call 1800 033 111

Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings. Do not use at temperatures below 10C, or when the temperature of surface may fall below 10C during the drying period. Avoid exposure to steam and condensation for 48 hours after application. Although the film is dry to touch in 30 minutes allow 7 days for film to fully cure before washing. Tinted Colours: Ensure that the paint is thoroughly shaken and stirred immediately after addition of tinter to the can and again before use.

Transport and Storage

Pack A 194-20810

Sizes 15 Litre

Weight 25 Kg

Dangerous Goods Class NA

Shipment Name Not dangerous goods.; No special transport requirements.

Flash point NA

UN Number NA

Package Group NA

Data Sheet	DULUX AcraTex 950 Roll On 00 Interior		
DuSpec Data Code	AUDA1410	Page No	2 of 3
Issue No	1.0	Date Issued	14/12/2011



DATA SHEET



DULUX AcraTex 950 Roll On 00 Interior	
	Data Sheet No. AUDA1410

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "AcraTex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427

Data Sheet	DULUX AcraTex 950 Roll On 00 Interior		
DuSpec Data Code	AUDA1410	Page No	3 of 3
Issue No	1.0	Date Issued	14/12/2011