

Dulux Professional Hot Weather Thinner

AUDD0005

Part A	920-89933
---------------	-----------

Description
A thinner to ease application of water based paints in hot, dry or windy conditions or when such paints are applied over dry porous surfaces.


Features
Slows drying

Benefits
Maintains a wet edge to overcome brush drag, improves lapping

Uses
As an additive for easing application of water based acrylic paints under exceptionally fast drying conditions - high temperatures, low humidity, dry porous surfaces or wind. It is useful for both exterior and interior paints.

Precautions And Limitations
All preparation and painting must conform to AS2311: The Painting of Buildings. 50 ml per litre for all but the most severe conditions. Up to 100 ml may be used if necessary. This product works by slowing the drying process. Do not add under cool conditions (below 15C), when air circulation is poor or when the relative humidity is high.

Performance Guide			
Weather	NA	Heat Resistance	NA;
Water	NA	Solvent	NA
Abrasion	NA		

Typical Properties																											
Thinner	DO NOT THIN	Colour	A water white liquid.																								
Components	1	Number Of Coats	N/A																								
Toxicity	No toxic residues on drying. See also Health & Safety Section.	V.O.C. Level	1040																								
Meets GBCA VOC Requirement?	N/A	Sanding Properties	N/A																								
Mixing Ratio	N/A	Touch Dry	N/A																								
Clean Up	 Water																										
Clean Up Description	Thoroughly wash brushes in water before re-using																										
Application Conditions	<table border="0"> <tr> <td style="text-align: right;">Solids By Volume</td> <td style="text-align: center;">0</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td style="text-align: right;">Wet Film Per Coat (microns)</td> <td style="text-align: center;">0</td> <td></td> <td style="text-align: center;">0</td> </tr> <tr> <td style="text-align: right;">Dry Film Per Coat (microns)</td> <td style="text-align: center;">0</td> <td style="text-align: center;">0</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="text-align: right;">Recoat Time (min)</td> <td style="text-align: center;">NA</td> <td></td> <td></td> </tr> <tr> <td style="text-align: right;">Theoretical Spread Rate (m²/L)</td> <td></td> <td></td> <td></td> </tr> </table>			Solids By Volume	0				Min	Max	Recommended	Wet Film Per Coat (microns)	0		0	Dry Film Per Coat (microns)	0	0	0	Recoat Time (min)	NA			Theoretical Spread Rate (m ² /L)			
Solids By Volume	0																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)	0		0																								
Dry Film Per Coat (microns)	0	0	0																								
Recoat Time (min)	NA																										
Theoretical Spread Rate (m ² /L)																											

Application Guide	
Application Procedure And Equipment	• Not Applicable

Health And Safety			
MSDS Number	21757	Health Effects	For detailed information refer to the product label and the current Material Safety Data Sheet available from Customer Service. Dulux Professional For detailed information refer to the product label and the current Material Safety Data Sheet available from Customer Service. Dulux Professional
Personal	If swallowed, seek medical attention. KEEP OUT OF REACH OF CHILDREN	Protective Equipment	Hot Weather Thinner contains glycols.
In the case of emergency, please call 1800 033 111			

Transport And Storage			
Pack A	920-89933	Shipment Name	Not classified dangerous goods. No special transport.
Size 1 Litre	Weight 1.2 Kg		
Flash Point	NA	UN Number	NA
Dangerous Goods Class	C1	Package Group	MA

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427