

Dulux Super Enamel Semi Gloss

AUDD0028

Part A	378 LINE
Approvals	APAS 0015/3 (Vivid White Base only)

Description

DULUX Super Enamel Semi Gloss is an oil based, hard-wearing, long-life finish suitable for all interior surfaces. DULUX Super Enamel Semi Gloss is highly recommended for doors, architraves and timber trim in heavy traffic areas such as hallways and family rooms.

Features

- Oil based
- Hard wearing
- Water resistant
- Semi gloss finish

Benefits

- Provides a long lasting, tough, quality finish.
- Ideal for heavy traffic areas in commercial and domestic buildings.
- Suitable for all 'wet' or steamy areas.
- Aesthetic appeal of subdued gloss level suitable for walls & ceilings

Uses






Use DULUX Super Enamel Semi Gloss as a high quality semi gloss enamel finish on correctly primed or undercoated interior timber, masonry, plaster and metal surfaces. Its hard wearing properties suit it to areas subject to heavy traffic in commercial and industrial buildings.

Precautions And Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings. Tinter if added should be shaken and stirred in immediately and thoroughly. Do not apply if the surface temperature is below 10 degrees or when the temperature of surface may fall below 10 degrees during the drying period. All enamels will yellow with age. This can be accelerated by darkness, heat and exposure to ammonia from freshly painted acrylic paints and some cleaning agents, particularly during the drying period. Darker colours will show more signs of marking and scuffing than lighter colours. Dark colours provide a background against which any foreign material on the surface – even a thin clear film – can be seen as a localised difference of colour and/or gloss against the surrounding area. This is, unfortunately, endemic across all coating types, no matter what substrate they are applied over.

Performance Guide

Weather	Not recommended for exterior use.	Salt	Very good resistance to splash and spillage of non-caustic salt solution
Heat Resistance	Up to 120C. Premature yellow and embrittlement will occur if film subject to 120C continuously.	Water	Excellent resistance to condensation and water splash
Solvent	Resists alcohol, mineral turpentine and similar solvents.	Abrasion	Excellent
Acid	Fair	Alkali	Fair

Typical Properties																											
Gloss Level	35-45 at 60 degrees	Thinner	Mineral Turpentine																								
Colour	Machine tinted to a full range of colours from an extensive range of white and coloured bases.	Components	1																								
Toxicity	Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.	V.O.C. Level	< 391g/L untinted																								
Touch Dry	4 Hours																										
Clean Up	 Thinner																										
Clean Up Description	Clean all equipment with Mineral Turpentine.																										
Application Method	 Air Spray  Airless Spray  Brush  Roller																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Solids By Volume</td> <td style="text-align: center;">51</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td style="text-align: center;">63</td> <td style="text-align: center;">63</td> <td style="text-align: center;">63</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td style="text-align: center;">32</td> <td style="text-align: center;">32</td> <td style="text-align: center;">32</td> </tr> <tr> <td>Recoat Time (min)</td> <td style="text-align: center;">16 Hours</td> <td style="text-align: center;">Indefinite</td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td style="text-align: center;">16</td> <td style="text-align: center;">16</td> <td style="text-align: center;">16</td> </tr> </table>			Solids By Volume	51				Min	Max	Recommended	Wet Film Per Coat (microns)	63	63	63	Dry Film Per Coat (microns)	32	32	32	Recoat Time (min)	16 Hours	Indefinite		Theoretical Spread Rate (m²/L)	16	16	16
Solids By Volume	51																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)	63	63	63																								
Dry Film Per Coat (microns)	32	32	32																								
Recoat Time (min)	16 Hours	Indefinite																									
Theoretical Spread Rate (m²/L)	16	16	16																								

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> Remove grease, oil, etc. by washing with a commercial paint cleaner. Thoroughly rinse and allow to dry. Acid and alkali contamination should be removed by thorough rinsing with clean water. Efflorescence or mould on plaster, masonry or timber surfaces must be treated. Rust, millscale, oxide deposits, loose or flaking paint or other foreign material on metal surfaces should be removed in accordance with the requirements of the chosen system, then apply primer, sealer or undercoat as required.
Application Procedure And Equipment	<ul style="list-style-type: none"> Brush, roller, conventional and airless spray Stir contents thoroughly before and during use with a broad flat stirrer, using an upward lifting action. <p>Brush/Roller: This product can be applied by brush or roller straight from the can. Apply two full coats allowing 16 hours dry followed by light sanding between coats. If necessary up to 50 ml per litre of Mineral Turpentine may be added to ease application.</p> <p>Airless/Conventional Spray: Suitable for application by all standard spray equipment. Apply wet even coats. Up to 125 ml per litre of DULUX Spraying Thinner may be added to aid atomisation for application by conventional spray and up to 30 ml per litre for application by airless spray.</p>

Health And Safety			
MSDS Number	DLXGHSEN001003	Health Effects	For detailed information refer to the product label and the current Material Safety Data Sheet available through Customer Service. Health Effects: Splashes to the eye will cause eye irritation. When spraying, inhalation of mists and vapours may produce respiratory irritation and headaches. For detailed information refer to the product label and the current Material Safety Data Sheet available through Customer Service. Health Effects: Splashes to the eye will cause eye irritation. When spraying, inhalation of mists and vapours may produce respiratory irritation and headaches.
Flammability	Flammability: This product is flammable. Store and use away from sources of heat and ignition.	Protective Equipment	Personal Protective Equipment: Wear eye protection and when spraying or applying to broadwall areas wear a respirator with a combined vapour/particulate cartridge.
In the case of emergency, please call 1800 033 111			

Transport And Storage			
Pack A	378 LINE	Shipment Name	PAINTS, flammable liquid, high flash point.
Size 500 ml 1 Litre 4 Litre 10 Litre		Weight 0.8 Kg 1.5 Kg 6.0 Kg 14.7 Kg	
Flash Point	>23C	UN Number	1263
Dangerous Goods Class	3	Package Group	III

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427