

DULUX Tuscan Effects

PRODUCT CODE 658-82579

Data Sheet No. AUDD0044

APPROVALS NA

Description

DULUX Tuscan Effects is a 100% acrylic exterior paint for application to bricks, concrete, fibro cement and masonry. Formulated to create the soft look of Tuscany, Dulux Tuscan Effects paint will not streak from water staining, unlike lime-based finishes.

Features

Fashionable paint effects
 One product system
 Little expertise needed
 Flat finish

Benefits

Adds Tuscan faded looks and style to any location
 Uncomplicated and easy to apply by brush or roller
 Total confidence in achieving the desired effect
 No streaking as with lime based products

Uses

DULUX Tuscan Effects has been formulated as a one product system that provides a subtle patchy effect. It has been formulated to have sufficient open time to work the product in a random criss-cross pattern that is required to achieve the effect.

Performance Guide

Weather	Recommended for exterior use.	Salt	NA
Heat	Resists up to 60C.	Water	Resists prolonged exposure to rain and condensation
Solvent	Sensitive to hydrocarbons	Abrasion	Resists mild burnishing.
Acid	NA	Alkali	NA

Typical Properties and Application Data

Gloss Level	Flat paint effect	Thinner	Not recommended, however if particularly hot or windy 5% water may be added
Gloss Level Ind		Spread Rate	8.0sqm/L
Volume Solids	40.0	Components	1
Colour	Can be tinted in 20 Tuscan colours. Can also be tinted in 20 Suede colours.	Toxicity	Lead free. Dry film is non toxic and conforms to AS1647, Part 3.
Number of Coats	2	V.O.C Level	< 110g/L untinted
Wet film per coat	Recommended 188 µm	Touch Dry	1-2 Hours
Dry film per coat	Recommended 75 µm	Clean Up	Clean all equipment with water
Recoat	4 Hours		


Application Method


DULUX Tuscan Effects

Data Sheet No. AUDD0044

Application Guide**Surface Preparation****PREVIOUSLY PAINTED SURFACES**

No priming required if painting a sound painted surface. To test surface, cut through the existing paint with a sharp blade, press cellulose tape firmly across the cut and then rip the paint off. If the old paint or render comes off, it should be removed. Scrape off all loose or flaking paint. Sand all surfaces to a flat finish, wipe clean. Clean down powdery areas with a hose and stiff brush. Allow to dry, then apply 1 coat of DULUX Acrylic Primer Undercoat to all bare areas to even out porosity.

NEW BRICK, MASONRY, CONCRETE AND FIBRO CEMENT

Surfaces must be sealed with DULUX Acrylic Primer Undercoat. First fill holes with exterior masonry filler. Wash down with water using a stiff brush to remove all loose material. New cement render must be allowed to age for a minimum of 28 days.

Application Procedure and Equipment

DULUX Tuscan Effects paint usually requires 2 coats to achieve the desired effect. Stir well before use with a broad flat paddle, using an up and down scooping action. Using a brush, apply material to area not accessible with a roller. Then first coat can be applied with a roller (which is easier) or a brush if preferred. The second or final coat can be applied with a roller or a brush, should be finished off with a wide brush (100mm or wider) using random criss cross strokes to achieve a washed effect. Using a brush for the application of the second coat will provide a fuller effect with better opacity. Make sure to overlap criss-cross areas to achieve an even effect.

Brush & Roller

Notes

This product lightens in colour as it dries, and the "tuscan" effect will not become apparent for about 30 minutes at 25 C.

The end effect is very dependent on the technique of the painter.

The "tuscan" like effect will not be as obvious in lighter colours as it is in darker colours.

Health and Safety

MSDS Number 45450

Health Effects For detailed information refer to the product label and the current Material Safety Data Sheet available through Customer Service.
Health Effects: Splashes to the eye may cause eye irritation.

Protective Equipment Personal Protective Equipment: Wear eye protection.

In the case of emergency please call 1800 033 111

Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings. All preparation and painting must conform to AS2311: The Painting of Buildings. The temperature must be between 10C and 30C during application, and remain above 10C during drying. Under cool or humid conditions, allow longer times to dry. Due to the large particles present in this product, it is not recommended for spraying. Whilst this product has good durability over bricks, concrete, fibro cement and masonry, it is not recommended for use on timber where long term durability is required.

Transport and Storage

Pack A 658-82579

Sizes 1 Litre 4 Litre 10 Litre

Weight 1.3 Kg 5.2 Kg 13.0 Kg

Dangerous Goods Class NA

Shipment Name Not dangerous goods.; No special transport requirements.

Flash point NA

UN Number NA

Package Group NA

Data Sheet	DULUX Tuscan Effects		
DuSpec Data Code	AUDD0044	Page No	2 of 3
Issue No	11.0	Date Issued	14/12/2011



DATA SHEET



DULUX Tuscan Effects	
	Data Sheet No. AUDD0044

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427

Data Sheet	DULUX Tuscan Effects		
DuSpec Data Code	AUDD0044	Page No	3 of 3
Issue No	11.0	Date Issued	14/12/2011