

Dulux Professional Interior Acrylic Low Sheen

AUDD0167

Part A	587 LINE
Approvals	APAS 0260/3 (White, Deep, Ultra Deep & Extra Bright Bases only)

Description

DULUX PROFESSIONAL Interior Low Sheen Acrylic is a scrubbable long lasting low sheen, acrylic paint giving excellent interior performance. It is designed to give outstanding application properties and appearance.

Features

- Water Based
- Super acrylic paint
- Scrubbable and hardwearing
- Ease of Application

Benefits

- Same Day recoat, easy clean up and low odour
- Provides hardwearing properties and suitability for 'wet' areas
- Use on areas subject to hard wear and marking, easily cleaned
- Easy spreading and lapping on broadwall areas

Uses






DULUX PROFESSIONAL Interior Low Sheen Acrylic is a scrubbable low sheen to use on all interior walls and ceilings and particularly recommended for wall areas in family rooms, children's rooms and hallways. Can also be used in areas subject to steam and condensation.

Precautions And Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings.
Do not use at temperatures below 10C, or when the temperature of the surface may fall below 10C during the drying period. Avoid exposure to steam and condensation for 48 hours after application. Although the film is dry to touch in 30 minutes allow 7 days for film to fully cure before washing.
Tinted Colours: Ensure that the paint is thoroughly shaken and stirred immediately after addition of tinter to the can and again before use. Darker colours will show more signs of marking and scuffing than lighter colours - if you are considering using a dark colour in a high traffic area you may want to consider a higher sheen level or the use of a protective clear coat.

Performance Guide

Weather	Designed for interior use only. Not recommended for exterior use.	Heat Resistance	Softens and sticks to other painted surfaces over 70C.
Water	Suitable for use in wet areas.	Solvent	Sensitive to aromatic hydrocarbons and alcohols.
Abrasion	Good wet and dry burnish resistance and stain removal.		

Typical Properties																											
Gloss Level	5-10 at 60 degrees, 5-15 at 85 degrees	Thinner	Water																								
Colour	Machine Tinted to a full range of colours from an extensive range of white and coloured bases.	Components	1																								
Number Of Coats	2*	Toxicity	Lead free. Dry film is non-toxic and conforms to AS 1647, Part 3.																								
V.O.C. Level	<60g/L	Touch Dry	30 Minutes																								
Clean Up	 Water																										
Clean Up Description	Clean all equipment with water																										
Application Method	    Air Spray Airless Spray Brush Roller																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Solids By Volume</td> <td style="text-align: center;">37.3</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td style="text-align: center;">63</td> <td style="text-align: center;">63</td> <td style="text-align: center;">63</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td style="text-align: center;">23</td> <td style="text-align: center;">23</td> <td style="text-align: center;">23</td> </tr> <tr> <td>Recoat Time (min)</td> <td style="text-align: center;">2 Hours</td> <td style="text-align: center;">Indefinite</td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td style="text-align: center;">16</td> <td style="text-align: center;">16</td> <td style="text-align: center;">16</td> </tr> </table>			Solids By Volume	37.3				Min	Max	Recommended	Wet Film Per Coat (microns)	63	63	63	Dry Film Per Coat (microns)	23	23	23	Recoat Time (min)	2 Hours	Indefinite		Theoretical Spread Rate (m²/L)	16	16	16
Solids By Volume	37.3																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)	63	63	63																								
Dry Film Per Coat (microns)	23	23	23																								
Recoat Time (min)	2 Hours	Indefinite																									
Theoretical Spread Rate (m²/L)	16	16	16																								

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> All surfaces must be thoroughly cleaned and free of all loose dirt, dust, grease, loose or flaking paint, and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth, then apply primer, sealer or undercoat as required. On Plasterglass in Western Australia apply one coat of DULUX PROFESSIONAL Precoat Plaster Ceiler
Application Procedure And Equipment	<ul style="list-style-type: none"> *Some colours may require more than 2 coats to achieve full hiding. Brush, roller, conventional and airless spray Stir contents thoroughly before and during use with a broad flat stirrer using an upward action. Brush/Roller: Use a short nap roller. Pre-wet brushes and rollers with water before commencing application. Avoid excessive brushing or rolling back into the paint which has been drying for more than 3 minutes. Thinning not usually required. If necessary thin with up to 100 ml of water per litre to ease application. Under hot conditions up to 60 ml per litre of DULUX Hot Weather Thinner may be used. Airless/Conventional Spray: Suitable for application by all standard spray equipment. For conventional spraying up to 125 ml per litre of water may be added to aid atomisation. For airless spraying up to 30 ml per litre of water may be added to aid atomisation

Health And Safety			
MSDS Number	DLXGHCEN001081	Health Effects	For detailed information refer to the product label and the current Material Safety Data Sheet available through Customer Service. Health Effects: Splashes to the eye may cause irritation. When spraying, inhalation of mists may produce respiratory irritation.
Protective Equipment	Personal Protective Equipment: Wear eye protection and when spraying wear a dust mask.		
In the case of emergency, please call 1800 033 111			

Transport And Storage			
Pack A	587 LINE	Shipment Name	Not dangerous goods. No special transport requirements.
Size 4 Litre 10 Litre 15 Litre		Weight 5.7 Kg 14.0 Kg 21.2 Kg	
Flash Point	NA	UN Number	NA
Dangerous Goods Class	NA	Package Group	NA

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.
 DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427