

## DULUX Wash & Wear 101 Barrier Technology Low Sheen

PRODUCT CODE 564 LINE

Data Sheet No. AUDD1096

APPROVALS APAS-0260/3, AS3730, Part 3.

### Description

Dulux Wash & Wears 101 Barrier Technology™ creates a super tough acrylic finish that allows you to wipe away most common marks, scuffs and stains with a wet cloth. Dulux Wash & Wear Low Sheen is low odour and low VOC. Dulux Wash & Wear Low Sheen is highly recommended for walls in high traffic areas such as hallways and family rooms.

### Features

Water based  
Resists marking  
High practical opacity  
Low VOC, Low Odour

### Benefits

Easy application, quick drying  
Most marks can be removed with a soft wet cloth  
Even finish, two coat hiding power  
Almost no paint smells


### Uses

Use DULUX Wash & Wear Low Sheen on walls and ceilings where a durable, mark resistant finish is required

### Performance Guide

<b>Weather</b>	Designed for interior use only. Not recommended for exterior use.	<b>Heat</b>	Softens and sticks to other painted surfaces over 70C
<b>Water</b>	Suitable for use in wet areas	<b>Solvent</b>	Sensitive to aromatic hydrocarbons and alcohols
<b>Abrasion</b>	Good wet and dry burnish resistance and stain removal		

### Typical Properties and Application Data

<b>Gloss Level</b>	5-10 at 60 degrees, 10-20 at 85 degrees	<b>Thinner</b>	Water
<b>Gloss Level Ind</b>		<b>Spread Rate</b>	15.8 sqm/L
<b>Volume Solids</b>	38.0	<b>Components</b>	1
<b>Colour</b>	Machine tinted to a wide range of colours from white, deep, ultra deep and coloured bases.	<b>Toxicity</b>	Lead free. Dry film is non-toxic.
<b>Number of Coats</b>	2*	<b>V.O.C Level</b>	< 5 g/L after tinting with Dulux Low VOC tint
<b>Wet film per coat</b>	Recommended 63 µm	<b>Touch Dry</b>	30 Minutes
<b>Dry film per coat</b>	Recommended 24 µm	<b>Clean Up</b>	Clean all equipment with water
<b>Recoat</b>	2 Hours		



### Application Method



## DULUX Wash & Wear 101 Barrier Technology Low Sheen

<b>Data Sheet No.</b>	<b>AUDD1096</b>
-----------------------	-----------------

### Application Guide

#### Surface Preparation

All surfaces must be thoroughly cleaned and free of all loose dirt, dust, grease, loose or flaking paint, and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth, then apply primer, sealer or undercoat as required.

#### Application Procedure and Equipment

Stir contents thoroughly before and during use with a broad flat stirrer using an upward lifting action.

Brush/Roller: Use a medium nap roller. Pre-wet brushes and roller with water before commencing application. Avoid excessive brushing or rolling back into the paint which has been drying for more than 3 minutes.

Thinning not usually required, however, if necessary thin with up to 50 ml of water per litre to ease application under hot conditions.

Airless/Conventional Spray: Suitable for application by all standard spray equipment. For conventional spraying up to 125 ml per litre of water may be added to aid atomisation. For airless spraying up to 30 ml per litre of water may be added to aid atomisation.

Brush, roller and spray

#### Notes

\* Some colours may require more than the recommended number of coats to achieve full opacity.

### Health and Safety

**MSDS Number** 10929

**Health Effects** For detailed information refer to the product label and the current Material Safety Data Sheet available through Customer Service. Splashes to the eye may cause eye irritation. When spraying, inhalation of mists may produce respiratory irritation.

**Protective Equipment** Wear eye protection and when spraying wear a dust mask.

**In the case of emergency please call 1800 033 111**

### Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings. Do not use at temperatures below 10C, or when the temperature of surface may fall below 10C during the drying period. Avoid exposure to steam and condensation for 48 hours after application. Although the film is dry to touch in 30 minutes allow 7 days for film to fully cure before washing. Tinted Colours: Ensure that the paint is thoroughly shaken and stirred immediately after addition of tinter to the can and again before use.

### Transport and Storage

**Pack A** 564 LINE

**Sizes** 1 Litre 4 Litre 10 Litres 15 Litres

**Weight** 1.5 Kg 5.8 Kg 14.5 Kg 22.0 Kg

**Dangerous Goods Class** NA

**Shipment Name** Not dangerous goods.; No special transport requirements.

**Flash point** NA

**UN Number** NA

**Package Group** NA

<b>Data Sheet</b>	DULUX Wash & Wear 101 Barrier Technology Low Sheen		
<b>DuSpec Data Code</b>	AUDD1096	<b>Page No</b>	2 of 3
<b>Issue No</b>	31.0	<b>Date Issued</b>	14/12/2011



DATA SHEET



<b>DULUX Wash &amp; Wear 101 Barrier Technology Low Sheen</b>	
	<b>Data Sheet No. AUDD1096</b>

**Disclaimer**

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427

<b>Data Sheet</b>	DULUX Wash & Wear 101 Barrier Technology Low Sheen		
<b>DuSpec Data Code</b>	AUDD1096	<b>Page No</b>	3 of 3
<b>Issue No</b>	31.0	<b>Date Issued</b>	14/12/2011