

## Dulux Texture Fine

AUDD1226

<b>Part A</b>	195-85710
<b>Approvals</b>	NA

### Description

DULUX Fine Texture is a 100% acrylic sandy texture designed to beautify brick, masonry and fibre cement surfaces.

### Features

- Water based
- High build 100% Acrylic paint
- Easy roller application
- Sandy texture finish

### Benefits

- Same day recoat and clean up
- Proven durability at high film builds
- Achieves texture finish without special training or tools
- Low cost alternative to traditional rendering and texturing methods

### Uses




DULUX Fine Texture is a 100% acrylic texture paint for direct application to bricks, concrete, fibrocement and masonry. Formulated to create a tough, flexible, high build texture finish that unifies brick and masonry surfaces.

### Precautions And Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings. Do not apply at temperatures below 10C or when the temperature may fall below 10C during the drying period. In summer, paint on the shady side of the building. Do not apply during hot and windy conditions. To ease application, even out porosity and improve coverage, hose down porous surfaces such as concrete block before application. Paint directly on to the damp surface. Application commenced on a single area must be uninterrupted. If an area is missed it is best touched up when dry. For best results, work in pairs with one applicator applying the material and the second applicator 'laying off'.

### Performance Guide

<b>Weather</b>	Excellent resistance to weathering with minimal colour change and dirt pick up.	<b>Heat Resistance</b>	Softens and suffers from dirt pick up over 70 degrees.
<b>Water</b>	Resists prolonged rain and condensation.	<b>Solvent</b>	Sensitive to aromatic hydrocarbons and alcohols.
<b>Abrasion</b>	Good resistance to abrasion.		

Typical Properties																											
<b>Gloss Level</b>	0-5 at 60 degrees	<b>Thinner</b>	Water																								
<b>Colour</b>	Can be machine tinted to a wide range of pastel and medium depth colours.	<b>Components</b>	1																								
<b>Toxicity</b>	Lead free. Dry film is non-toxic.	<b>V.O.C. Level</b>	< 60g/L untinted																								
<b>Touch Dry</b>	1 hour																										
<b>Clean Up</b>	 Water																										
<b>Clean Up Description</b>	Clean all equipment with water																										
<b>Application Method</b>	  Brush      Roller																										
<b>Application Conditions</b>	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;"><b>Solids By Volume</b></td> <td style="text-align: center;">54</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;"><b>Min</b></td> <td style="text-align: center;"><b>Max</b></td> <td style="text-align: center;"><b>Recommended</b></td> </tr> <tr> <td><b>Wet Film Per Coat (microns)</b></td> <td style="text-align: center;">259</td> <td style="text-align: center;">259</td> <td style="text-align: center;">259</td> </tr> <tr> <td><b>Dry Film Per Coat (microns)</b></td> <td style="text-align: center;">140</td> <td style="text-align: center;">140</td> <td style="text-align: center;">140</td> </tr> <tr> <td><b>Recoat Time (min)</b></td> <td style="text-align: center;">4 Hours</td> <td style="text-align: center;">Indefinite</td> <td></td> </tr> <tr> <td><b>Theoretical Spread Rate (m<sup>2</sup>/L)</b></td> <td style="text-align: center;">3.9</td> <td style="text-align: center;">3.9</td> <td style="text-align: center;">3.9</td> </tr> </table>			<b>Solids By Volume</b>	54				<b>Min</b>	<b>Max</b>	<b>Recommended</b>	<b>Wet Film Per Coat (microns)</b>	259	259	259	<b>Dry Film Per Coat (microns)</b>	140	140	140	<b>Recoat Time (min)</b>	4 Hours	Indefinite		<b>Theoretical Spread Rate (m<sup>2</sup>/L)</b>	3.9	3.9	3.9
<b>Solids By Volume</b>	54																										
	<b>Min</b>	<b>Max</b>	<b>Recommended</b>																								
<b>Wet Film Per Coat (microns)</b>	259	259	259																								
<b>Dry Film Per Coat (microns)</b>	140	140	140																								
<b>Recoat Time (min)</b>	4 Hours	Indefinite																									
<b>Theoretical Spread Rate (m<sup>2</sup>/L)</b>	3.9	3.9	3.9																								

Application Guide	
<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>All surfaces must be thoroughly cleaned and free of all dirt, loose and flaking paint. Efflorescence or mould must be treated before application of paint. New concrete, mortar or cement render must be allowed to cure for 4 to 8 weeks depending on concrete thickness and drying conditions. Fill holes with grouting cement. Wash down with water using a stiff brush to remove all loose material. To test the adhesion of previously painted surfaces, cut an 'X' through the existing paint with a sharp blade, press cellulose tape firmly across the cut and then rip the tape off. If the old paint or render comes off, it should be removed.</li> </ul>
<b>Application Procedure And Equipment</b>	<ul style="list-style-type: none"> <li>Long Nap Roller (12mm recommended)</li> <li>Stir contents thoroughly before and during use with a broad flat paddle, using an up and down scooping action. Using a brush, apply material to edges, internal angles and areas not accessible with a roller. Finish brush applied sections with a dabbing motion. Generously load the roller and apply from the ground upwards in vertical strips of 1/2 to 1 metre lengths. Reload the roller after each strip and repeat until 3 or 4 strips are applied. Even out material by rolling diagonally across the surface. Apply another strip of wet material to keep a working wet edge and then lay off the previously spread area in either an upward or downward motion to give an even finish. Working in a team can help maintain the wet edge by moving along more quickly. Two coats are normally required to yield a uniform even texture but this will depend upon application technique and the condition of the substrate.</li> </ul>

Health And Safety			
<b>MSDS Number</b>	20365, 0	<b>Health Effects</b>	For detailed information refer to the product label and the current Material Safety Data Sheet available through Dulux Customer Service. Health Effects: Splashes to the eye may cause eye irritation For detailed information refer to the product label and the current Material Safety Data Sheet available through Dulux Customer Service. Health Effects: Splashes to the eye may cause eye irritation
<b>Protective Equipment</b>	Wear eye protection.		
<b>In the case of emergency, please call 1800 033 111</b>			

Transport And Storage			
<b>Pack A</b>	195-85710	<b>Shipment Name</b>	Not dangerous goods.; No special transport requirements.
<b>Size</b> 4 litre 10 litre	<b>Weight</b> 6.0 Kg 15.5 Kg		
<b>Flash Point</b>	NA	<b>UN Number</b>	NA
<b>Dangerous Goods Class</b>	NA	<b>Package Group</b>	NA

**Disclaimer**

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.  
 DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427