

DULUX 1 Step Oil Based Primer Sealer U/coat (Old)

PRODUCT CODE 360-89141

Data Sheet No. AUDD1227

APPROVALS APAS-0181

Description

DULUX Oil Based Primer Sealer Undercoat is an interior/exterior prep coat with excellent hiding, filling and sanding properties and good hold-out for enamel topcoats.

Features

All purpose primer sealer undercoat
 Excellent opacity
 Excellent filling and sandability

Benefits

Can be used on a wide range of interior and exterior surfaces.
 Quick and easy application with good hiding power.
 Great finish for subsequent topcoats.

Uses

Use DULUX Oil Based Primer Sealer Undercoat is ideal for use over bare interior and exterior timber. Can also be used on masonry surfaces.

Performance Guide

Weather Excellent as part of system using approved topcoat.

Heat Up to 120C. Yellowing and embrittlement will occur if film is subject to 120C heat continuously.

Water Resists rain and condensation for prolonged periods when used as part of system.


Solvent Resists alcohols and hydrocarbon. Film is liable to attack from other strong solvents.

Abrasion NA

Typical Properties and Application Data

Gloss Level Flat

Gloss Level Ind



Volume Solids 50.4

Colour White

V.O.C Level < 395g/L untinted

Wet film per coat Recommended 62 µm

Dry film per coat Recommended 31 µm

Recoat 16 Hours

Thinner Mineral Turpentine

Spread Rate 16.3 sqm/L

Components 1

Toxicity Lead free. Dry film is non-toxic.

Sanding Properties Excellent

Touch Dry 6 Hours

Clean Up Clean all equipment with mineral turpentine.



Application Method



DULUX 1 Step Oil Based Primer Sealer U/coat (Old)

Data Sheet No. AUDD1227

Application Guide**Surface Preparation**

All surfaces must be thoroughly dry, clean and free of all loose dirt, surface chalk, grease, mould, mildew and wax, loose or flaking paint.

For weathered timber, sand back to fresh timber and dust off.

For interior timber, lightly sand and dust off.

Apply 1 coat of Dulux 1 Step Oil Based Primer Sealer Undercoat.

Can be used on most interior and exterior masonry surfaces but other prepcoats such as Dulux 1 Step Acrylic Primer Sealer Undercoat may be preferred.

New interior set plaster: Use DULUX Sealer Binder.

Application Procedure and Equipment

Stir contents thoroughly before and during use with a broad flat stirrer using an upward lifting action.

Brush/Roller: Apply one or two coats to the prepared surface. Thinning if necessary with up to 50 ml/litre of Mineral Turpentine.

Spray: If necessary thin with DULUX Spraying Thinner with up to 50 ml per litre.

Brush, roller or spray.

Health and Safety

MSDS Number 20227

Health Effects For detailed information refer to the product label and the current Material Safety Data Sheet available through Customer Service.
Health Effects: Splashes to the eye will cause eye irritation. When spraying, inhalation of mists and vapours may produce respiratory irritation and headaches.

Flammability This product is flammable. Store and use away from sources of heat and ignition.

Protective Equipment Wear eye protection and when spraying or applying to broadwall areas wear a respirator with a combined vapour/particulate cartridge.

In the case of emergency please call 1800 033 111

Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings.

Do not apply if the surface temperature is below 10C or conditions indicate it will fall below 10C during the drying period.

Do not apply externally when weather is doubtful, or late in the afternoon during winter, as frost, rain or dew on the uncured undercoat may result in loss of film integrity and impair durability of the system.

Transport and Storage

Pack A 360-89141

Sizes 500 ml 1 Litre 4 Litre 10 Litre

Weight 0.8 Kg 1.6 Kg 6.3 Kg 15.7 Kg

Dangerous Goods Class 3

Shipment Name PAINTS, flammable liquid, high flash point.

Flash point >23C

UN Number 1263

Package Group III

Data Sheet	DULUX 1 Step Oil Based Primer Sealer U/coat (Old)		
DuSpec Data Code	AUDD1227	Page No	2 of 3
Issue No	7.0	Date Issued	14/12/2011

Dulux**DuSpec****DATA SHEET****Dulux****DULUX 1 Step Oil Based Primer Sealer U/coat (Old)****Data Sheet No. AUDD1227****Disclaimer**

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427

Data Sheet	DULUX 1 Step Oil Based Primer Sealer U/coat (Old)		
DuSpec Data Code	AUDD1227	Page No	3 of 3
Issue No	7.0	Date Issued	14/12/2011