

Dulux Texture Medium

AUDD1228

Part A	195-85715
Approvals	NA

Description
DULUX Medium Texture is a sandy bagged texture designed to modernise brick, masonry and fibre cement surfaces.



Features
<ul style="list-style-type: none"> • Water based • High build 100% Acrylic paint • Easy application • Bagged texture finish

Benefits
<ul style="list-style-type: none"> • Same day recoat and clean up • Proven durability at high film builds • Achieves texture finish without special training • Low cost alternative to traditional rendering and texturing methods

Uses
DULUX Medium Texture is a 100% acrylic texture paint for direct application to bricks, concrete, fibrocement and masonry. Formulated to create a tough, flexible, high build bagged texture finish that modernises brick and masonry surfaces.

Precautions And Limitations
All preparation and painting must conform to AS2311: The Painting of Buildings. Do not apply at temperatures below 10C or when the temperature may fall below 10C during the drying period. In summer, paint on the shady side of the building. Do not apply during hot and windy conditions. Protect from rain for 24 hours after application.

Performance Guide			
Weather	Excellent resistance to weathering with minimal colour change and dirt pick up.	Heat Resistance	Softens and suffers from dirt pick up over 70 degrees.
Water	Resists prolonged rain and condensation.	Solvent	Sensitive to aromatic hydrocarbons and alcohols.
Abrasion	Good resistance to abrasion.		

Typical Properties																											
Gloss Level	0-5 at 60 degrees	Thinner	Water																								
Colour	Can be tinted to a wide range of pastel and medium depth colours.	Components	1																								
Toxicity	Lead free. Dry film is non-toxic.	V.O.C. Level	< 60g/L untinted																								
Touch Dry	1 hour																										
Clean Up	 Water																										
Clean Up Description	Clean all equipment with water																										
Application Method	 Roller																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: right;">Solids By Volume</td> <td style="text-align: center;">53</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td style="text-align: right;">Wet Film Per Coat (microns)</td> <td style="text-align: center;">358</td> <td style="text-align: center;">358</td> <td style="text-align: center;">358</td> </tr> <tr> <td style="text-align: right;">Dry Film Per Coat (microns)</td> <td style="text-align: center;">190</td> <td style="text-align: center;">190</td> <td style="text-align: center;">190</td> </tr> <tr> <td style="text-align: right;">Recoat Time (min)</td> <td style="text-align: center;">4 Hours</td> <td style="text-align: center;">Indefinite</td> <td></td> </tr> <tr> <td style="text-align: right;">Theoretical Spread Rate (m²/L)</td> <td style="text-align: center;">2.8</td> <td style="text-align: center;">2.8</td> <td style="text-align: center;">2.8</td> </tr> </table>			Solids By Volume	53				Min	Max	Recommended	Wet Film Per Coat (microns)	358	358	358	Dry Film Per Coat (microns)	190	190	190	Recoat Time (min)	4 Hours	Indefinite		Theoretical Spread Rate (m²/L)	2.8	2.8	2.8
Solids By Volume	53																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)	358	358	358																								
Dry Film Per Coat (microns)	190	190	190																								
Recoat Time (min)	4 Hours	Indefinite																									
Theoretical Spread Rate (m²/L)	2.8	2.8	2.8																								

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> All surfaces must be thoroughly cleaned and free of all dirt, loose and flaking paint. Efflorescence or mould must be treated before application of paint. New concrete, mortar or cement render must be allowed to cure for 4 to 8 weeks depending on concrete thickness and drying conditions. Fill holes with grouting cement. Wash down with water using a stiff brush to remove all loose material. To test the adhesion of previously painted surfaces, cut an 'X' through the existing paint with a sharp blade, press cellulose tape firmly across the cut and then rip the tape off. If the old paint or render comes off, it should be removed. <p>On porous surfaces, applying a priming coat of Dulux Texture Primer will condition the surface and help aid application of additional coats.</p>
Application Procedure And Equipment	<ul style="list-style-type: none"> Long Nap Roller (12mm recommended) and sponge or mitt Stir contents thoroughly before and during use with a broad flat paddle, using an up and down scooping action. Application is in 2 parts: Delivery (via a roller) and Finishing (using a sponge, brush or mitt) <p>DELIVERY: generously load the roller and apply from the ground upwards in vertical strips of 1/2 to 1 metre lengths. Reload the roller after each strip and repeat until 3 or 4 strips are applied. Even out material by rolling diagonally across the surface. It is important to work swiftly to allow time for the finishing process and this can be best achieved by working in a team, with one "delivering" and the other "finishing".</p> <p>FINISHING: working with a clean bucket of water and a sponge (we recommend a fine cell sponge) or mitt, wet the sponge or mitt and, working in a circular motion, sponge finish the applied material to obliterate the roller pattern, fill mortar joints and/or cover surface imperfections. Clean out the sponge in the water and lightly finish in larger circular strokes. Depending upon the finishing pressure and material retained from the sponge, varied finishing effects can be achieved, from a light "mottled" effect to a more prominent "swirl" pattern.</p> <p>Repeat the above delivery and finishing procedure, maintaining a working wet edge, until completed. 2 coats are recommended but additional coats may be required depending upon the depth of the mortar joints.</p>

Health And Safety			
MSDS Number	20366, 0	Health Effects	For detailed information refer to the product label and the current Material Safety Data Sheet available through Dulux Customer Service. Health Effects: Splashes to the eye may cause eye irritation For detailed information refer to the product label and the current Material Safety Data Sheet available through Dulux Customer Service. Health Effects: Splashes to the eye may cause eye irritation
Protective Equipment	Wear eye protection.		
In the case of emergency, please call 1800 033 111			

Transport And Storage			
Pack A	195-85715	Shipment Name	Not dangerous goods.; No special transport requirements.
Size 10 litre		Weight 15.5 Kg	
Flash Point	NA	UN Number	NA
Dangerous Goods Class	NA	Package Group	NA

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.
 DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427