

Dulux Prepcoat Acrylic Sealer Undercoat

AUDD1402

Part A	630-84191
Approvals	APAS-0172, APAS-0163/2

Description

Dulux Acrylic Sealer Undercoat is suitable for all interior surfaces. It is especially designed for sealing and undercoating interior masonry and paperfaced wallboard. Dulux Acrylic Sealer Undercoat's unique Ultrasmooth™ Technology helps to eliminate the traditional problems of surface imperfections, as its high build allows it to fill minor cracks and defects. Dulux Acrylic Sealer Undercoat has excellent hiding power and sanding properties. It is a low VOC and low odour water based prepcoat. Dulux Acrylic Sealer Undercoat is highly recommended wherever a smooth finish is required.

Features

- Ease of application
- Universal & multipurpose
- Dual purpose
- <5g/L VOC

Benefits

- Excellent spreading, wet edge, quick to apply, quick drying
- Can be used under either oil based or water based topcoats
- Doubles as both a sealer and undercoat for most work
- Low odour

Uses






DULUX Acrylic Sealer Undercoat is suitable for sealing and undercoating Interior paper faced wallboards, render and hardboards. Suitable for use under both water or solvent borne topcoats. It is also designed for painting over roughly textured products such as Dulux Design™ Suede and Dulux Design Stone. Dulux Acrylic Sealer Undercoat is highly recommended wherever a smooth finish is required.

Precautions And Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings.
 Do not apply when the temperature is 10C or under or likely to fall below 10C during the drying period.
 Tinter if added should be shaken and stirred in immediately and thoroughly.
 Do not overspread, or exceed the recommended rate of 16 square metres per litre.

Performance Guide

Weather	Interior use only.	Heat Resistance	Resists temperatures up to 60 degrees.
Water	Resists mild & intermittent exposure to steam & condensation as part of system.	Solvent	Sensitive to aromatic hydrocarbons and alcohols.
Abrasion	Not applicable		

Typical Properties																											
Gloss Level	Flat	Thinner	Water																								
Colour	White. May be tinted with DULUX Decorama Tinters up to 25 ml per litre.	Components	1																								
Number Of Coats	1	Toxicity	Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.																								
V.O.C. Level	<5 g/L	Meets GBCA VOC Requirement?	Yes. Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.																								
Touch Dry	20 Minutes																										
Clean Up	 Water																										
Clean Up Description	Clean all equipment immediately with water.																										
Application Method	 Air Spray  Airless Spray  Brush  Roller																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Solids By Volume</td> <td style="text-align: center;">35</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td style="text-align: center;">63</td> <td style="text-align: center;">63</td> <td style="text-align: center;">63</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td style="text-align: center;">22</td> <td style="text-align: center;">22</td> <td style="text-align: center;">22</td> </tr> <tr> <td>Recoat Time (min)</td> <td style="text-align: center;">2 Hours</td> <td style="text-align: center;">Indefinite</td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td style="text-align: center;">12</td> <td style="text-align: center;">12</td> <td style="text-align: center;">12</td> </tr> </table>			Solids By Volume	35				Min	Max	Recommended	Wet Film Per Coat (microns)	63	63	63	Dry Film Per Coat (microns)	22	22	22	Recoat Time (min)	2 Hours	Indefinite		Theoretical Spread Rate (m²/L)	12	12	12
Solids By Volume	35																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)	63	63	63																								
Dry Film Per Coat (microns)	22	22	22																								
Recoat Time (min)	2 Hours	Indefinite																									
Theoretical Spread Rate (m²/L)	12	12	12																								

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> Previously painted surfaces: Thoroughly clean all surfaces free of loose dust, surface chalk, grease, mould, mildew, wax and loose or flaking paint. Wash with sugar soap. Treat mould contaminated areas with antimould. Rinse with clean water. Fill nail holes, imperfections and cracks with a suitable filler, sand and dust off. For use on paperfaced plasterboard and masonry. On bare set plaster, use 1 coat of DULUX Sealer Binder.
Application Procedure And Equipment	<ul style="list-style-type: none"> Brush, roller, conventional and airless spray. Stir contents thoroughly before and during use with a broad, flat stirrer using an upward lifting action. Brush/Roller: Pre-wet brushes and roller with water prior to use. A short or medium nap roller will give most uniform appearance. Apply a full even coat and finish by light parallel strokes with a practically dry roller. Conventional/Airless Spray: Suitable for application by all standard spray equipment.

Health And Safety				
MSDS Number	14543087, 0	<table border="0" style="width: 100%;"> <tr> <td style="width: 30%;">Health Effects</td> <td>For detailed information refer to the product label and the current Material Safety Data Sheet available through Customer Service. Health Effects: Splashes to the eye may cause eye irritation. When spraying, inhalation of mists may produce respiratory irritation.. For detailed information refer to the product label and the current Material Safety Data Sheet available through Customer Service. Health Effects: Splashes to the eye may cause eye irritation. When spraying, inhalation of mists may produce respiratory irritation..</td> </tr> </table>	Health Effects	For detailed information refer to the product label and the current Material Safety Data Sheet available through Customer Service. Health Effects: Splashes to the eye may cause eye irritation. When spraying, inhalation of mists may produce respiratory irritation.. For detailed information refer to the product label and the current Material Safety Data Sheet available through Customer Service. Health Effects: Splashes to the eye may cause eye irritation. When spraying, inhalation of mists may produce respiratory irritation..
Health Effects	For detailed information refer to the product label and the current Material Safety Data Sheet available through Customer Service. Health Effects: Splashes to the eye may cause eye irritation. When spraying, inhalation of mists may produce respiratory irritation.. For detailed information refer to the product label and the current Material Safety Data Sheet available through Customer Service. Health Effects: Splashes to the eye may cause eye irritation. When spraying, inhalation of mists may produce respiratory irritation..			
Protective Equipment	Personal Protective Equipment: Wear eye protection and when spraying wear a dust mask.			
In the case of emergency, please call 1800 033 111				

Transport And Storage			
Pack A	630-84191	Shipment Name	Not dangerous goods.; No special transport requirements.
Size 500 ml 1 Litre 4 Litre 10 Litre 15 Litre		Weight 0.7 Kg 1.5 Kg 6 Kg 14.6 Kg 22 Kg	
Flash Point	NA	UN Number	NA
Dangerous Goods Class	NA	Package Group	NA

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427