

Dulux Professional Ceiling Paint Black Flat

AUDD1472

Part A	615-00070
---------------	-----------

Description
DULUX PROFESSIONAL Ceiling Paint Black is a water based, interior, low VOC flat designed specifically for use on ceilings, and for blacking out ceiling cavities.






Features
<ul style="list-style-type: none"> • Water based • Low odour • Low VOC, <2g/L • Dead flat finish • Factory packed colour

Benefits
<ul style="list-style-type: none"> • Same day recoat, easy clean up. • No lingering paint odours • Can be used on Greenstar projects • Hides minor surface imperfections, giving a smooth even finish • Excellent opacity

Uses
Use DULUX PROFESSIONAL Ceiling Paint Black on ceilings where a dead flat finish is required. This product is a factory packed colour, targetted towards the Commercial market, where there is a need to black out pipework in Ceiling cavities. Do not use in areas that will require frequent cleaning.

Precautions And Limitations
All preparation and painting must conform to AS2311: The Painting of Buildings. Do not paint at temperatures below 10C or when the temperature of surface may fall below 10C during the drying period. This product is designed for use on ceilings, so is not recommended for high traffic areas, or areas requiring frequent cleaning.

Performance Guide			
Weather	Not suitable for exterior use.	Water	Not recommended for "wet" areas.
Solvent	Sensitive to alcohols, aromatic hydrocarbons and ketones.		

Typical Properties																																	
Gloss Level	0-1 at 85 degrees.	Thinner	Water																														
Colour	Factory packed colour, not tintable.	Components	1																														
Toxicity	Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.	V.O.C. Level	< 2 g/L inclusive of Dulux low VOC tinter																														
Meets GBCA VOC Requirement?	Yes. Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.	Touch Dry	20 Minutes																														
Clean Up	 Water																																
Clean Up Description	Clean all equipment with water.																																
Application Method	 Air Spray	 Airless Spray	 Brush																														
			 Roller																														
Application Conditions	<table border="1"> <thead> <tr> <th colspan="2">Solids By Volume</th> <th>32</th> <th></th> <th></th> </tr> <tr> <th></th> <th>Min</th> <th></th> <th>Max</th> <th>Recommended</th> </tr> </thead> <tbody> <tr> <td>Wet Film Per Coat (microns)</td> <td>69</td> <td></td> <td>69</td> <td>69</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td>22</td> <td></td> <td>22</td> <td>22</td> </tr> <tr> <td>Recoat Time (min)</td> <td>2 Hours</td> <td></td> <td>Indefinite</td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td>14.5</td> <td></td> <td>14.5</td> <td>16</td> </tr> </tbody> </table>			Solids By Volume		32				Min		Max	Recommended	Wet Film Per Coat (microns)	69		69	69	Dry Film Per Coat (microns)	22		22	22	Recoat Time (min)	2 Hours		Indefinite		Theoretical Spread Rate (m ² /L)	14.5		14.5	16
Solids By Volume		32																															
	Min		Max	Recommended																													
Wet Film Per Coat (microns)	69		69	69																													
Dry Film Per Coat (microns)	22		22	22																													
Recoat Time (min)	2 Hours		Indefinite																														
Theoretical Spread Rate (m ² /L)	14.5		14.5	16																													

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> All surfaces must be thoroughly cleaned and free of all dirt, dust & grease. Scrape off any loose or flaking paint, and dust off any loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth, then apply primer, sealer or undercoat as required.
Application Procedure And Equipment	<ul style="list-style-type: none"> Brush, roller, conventional or airless spray. Stir contents thoroughly before and during use with a broad flat stirrer, using an upward lifting action. <p>Brush/Roller: Rinse brush or roller in water before starting and use while still slightly damp. Under hot conditions or on very absorbent surfaces, up to 100ml clean water may be added per litre to assist application.</p> <p>Airless/Conventional Spray: Suitable for application by all standard spray equipment. If necessary thin with up to 100ml per litre of water to aid atomisation.</p>

Health And Safety			
MSDS Number	14550927	Health Effects	For detailed information refer to the current Material Safety Data Sheet available through Customer Service.
Personal	Splashes to the eye may cause irritation. When spraying, inhalation of mists may produce respiratory irritation.	Protective Equipment	Personal Protective Equipment: Wear eye protection, and when spraying wear a dust mask.
Disposal	<p>Do not pour left over paint down the drain. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collections.</p> <p>Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle the container via recycling programs. Disposal of empty containers via domestic recycling programs may differ between local authorities. Check with your local council first.</p> <p>Alternatively, keep unwanted paint in sealed containers for disposal via special chemical waste collections.</p>		
In the case of emergency, please call 1800 033 111			

Transport And Storage			
Pack A	615-00070	Shipment Name	Not dangerous goods. No special transport requirements.
Size 15 Litre		Weight 18.5 Kg	
Flash Point	NA	UN Number	NA
Dangerous Goods Class	NA	Package Group	NA

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.
 DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427