

**INTERGRAIN Liquid 8 Paint Remover**

PRODUCT CODE 552-94807

Data Sheet No. AUDW0766

APPROVALS NA

**Description**

Intergrain Liquid 8 is a fast acting, easy to use, water soluble gel timber finish and paint remover. Liquid 8s low odour and non-drip, citrus based gel formula allows for a safe and easy application on all horizontal and vertical surfaces. With excellent softening and penetration, it quickly and effectively removes most water and solvent based coatings including marine, automotive and industrial paints, acrylics, polyurethanes and varnishes. Liquid 8 is gentle on the surface and will not darken timber like some traditional strippers.

**Features**

Gel structure  
Caustic free  
Gentle on the surface

**Benefits**


Won't run onto other areas  
Safer to use  
Won't darken timber

**Uses**

Use on all interior and exterior timber, metal, brick and masonry surfaces.

**Performance Guide**

**Typical Properties and Application Data**

<b>Gloss Level</b>	N A	<b>Thinner</b>	DO NOT THIN
<b>Spread Rate</b>	4.0sqm/L	<b>Volume Solids</b>	5.0
<b>Components</b>	1	<b>Toxicity</b>	Normally safe to handle when used in accordance with the specified conditions
<b>Number of Coats</b>	1 or 2	<b>V.O.C Level</b>	< 895g/L
<b>Wet film per coat</b>	Recommended 0 µm		
<b>Dry film per coat</b>	Recommended 0 µm		
<b>Application Method</b>			

# INTERGRAIN Liquid 8 Paint Remover

<b>Data Sheet No.</b>	<b>AUDW0766</b>
-----------------------	-----------------

## Application Guide

### Surface Preparation

Protect any adjoining areas that you do not wish to strip.

Apply a thick coat by broad synthetic bristle brush. Do not exceed coverage rates.

Allow 15-30 minutes to penetrate and wrinkle or blister the coating. Times will vary depending on the type of finish and thickness of the coating to be removed. For best results cover with a plastic dropsheet to stop Liquid 8 from drying out.

Test with a scraper to ensure that the paint is easily removed.

Remove using a paint scraper or if appropriate a high pressure water cleaner. On timber surfaces, work in the direction of the grain. On curved or rough surfaces or mouldings use a synthetic hard bristle brush or scourer.

Do not allow Liquid 8 to dry on the surface.

For best results work in small areas at a time.

Thick or stubborn coatings may require more than one application.

Clean stripped surfaces thoroughly with water and allow to dry.

Sand as necessary to remove any residue before refinishing the surface.

### Application Procedure and Equipment

Brush

### Notes

SPREADING RATES

Approximately 4 m<sup>2</sup>/L

<b>Data Sheet</b>	INTERGRAIN Liquid 8 Paint Remover		
<b>DuSpec Data Code</b>	AUDW0766	<b>Page No</b>	2 of 4
<b>Issue No</b>	9.0	<b>Date Issued</b>	14/12/2011

**INTERGRAIN Liquid 8 Paint Remover**
**Data Sheet No.** AUDW0766

**Health and Safety**
**MSDS Number** 146075

**Using Safety Precautions** Provide adequate ventilation. If using inside keep windows and doors open during use and while drying.

**Health Effects** FIRST AID: If poisoning occurs, contact a doctor or Poisons Information Centre. Phone 13 11 26.  
 SWALLOWED: If swallowed, DO NOT induce vomiting, Give a glass of water. Seek medical advice.  
 EYE: If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.  
 SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.  
 INHALED: Remove from contaminated area. Seek medical advice if effects persist.

**Flammability** This product is flammable. Eliminate all sources of ignition. Do not smoke. Keep containers closed when not in use.

**Fire Suppression** Water fog, foam, dry agent. Avoid breathing products of combustion.

**Protective Equipment** Wear eye protection, protective clothing and gloves, and if spraying, wear a respirator with a combined vapour/particulate cartridge.

**Storage** Keep out of reach of children.

**Disposal** Do not pour leftover product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council/Waste Management Authority first.

**In the case of emergency please call 1800 033 111**
**Precautions and Limitations**

Protect adjoining surfaces. If removing by hosing down, ensure run-off does not come into contact with plants etc. Wear safety gloves, safety glasses and cover feet and arms with protective clothing.

**Transport and Storage**
**Pack A** 552-94807

**Sizes** 1 Litre 500 MI 250 MI

**Weight** 1.1 Kg 550 Gm 320 Gm

<b>Data Sheet</b>	INTERGRAIN Liquid 8 Paint Remover		
<b>DuSpec Data Code</b>	AUDW0766	<b>Page No</b>	3 of 4
<b>Issue No</b>	9.0	<b>Date Issued</b>	14/12/2011



# DATA SHEET



## INTERGRAIN Liquid 8 Paint Remover

Data Sheet No. AUDW0766

### Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427

<b>Data Sheet</b>	INTERGRAIN Liquid 8 Paint Remover		
<b>DuSpec Data Code</b>	AUDW0766	<b>Page No</b>	4 of 4
<b>Issue No</b>	9.0	<b>Date Issued</b>	14/12/2011