

## Intergrain Reviva

AUDW0767

<b>Part A</b>	552 94814
---------------	-----------

### Description

Intergrain Reviva is a high strength cleaner that contains oxalic acid and citric acid, both naturally occurring, bio-degradable organic acids. Use Reviva to clean all timber prior to coating. Reviva will help restore and prepare weathered, grey, rust or tannin stained, mould or mildew affected timber to a clean appearance ready for coating. When used in combination with Intergrain PowerPrep™\*, Reviva can also be used to avoid the weathering process, and enable immediate coating of new bare timber. Specially formulated PowerPrep helps draw out the tannins and oils quickly and removes them from the new timber surface. Then, Reviva cleans the timber and prepares it for coating.

^ENHANCED DWD TRISHIELD APPLICATION SYSTEM: Intergrain Reviva Timber Cleaner (STAGE 1), then Intergrain Dimension 4™ UltraPrimer™\* (STAGE 2), then Intergrain DWD™\* (STAGE 3). ALWAYS apply DWD in accordance with this process to ensure maximum lifespan from the coating.

#NATURAL CLEANING POWER  
Reviva is a high strength cleaner that contains oxalic acid and citric acid, both naturally occurring, bio-degradable organic acids.

### Features

- High strength.
- Cleans and prepares timber for coating.
- Contains oxalic acid and citric acid.

### Benefits

- Clean all timber prior to coating.
- Restores and prepares weathered, grey, rust or tannin stained, mould or mildew affected timber to a clean appearance ready for coating.
- Bio-degradable organic acids.

### Uses

On all exterior timber including decking, outdoor furniture, weatherboards, pergolas, fences and marine timbers.


### Precautions And Limitations

Avoid contact with painted, concrete or metal surfaces and vegetation. May be corrosive to metals. Rinse off thoroughly if contact occurs. Reviva is not designed to remove paint or other timber coatings.

### Performance Guide

<b>Weather</b>	Exterior use only.
----------------	--------------------

### Typical Properties

<b>Thinner</b>	Water	<b>Colour</b>	Yellow
<b>Components</b>	1	<b>Toxicity</b>	POISON
<b>V.O.C. Level</b>	< 10g/L	<b>Meets GBCA VOC Requirement?</b>	Yes. Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.
<b>Clean Up</b>	 Water		
<b>Application Method</b>	<b>Other:</b> Stiff bristle brush, broom or scouring pad.		
<b>Typical Properties Notes</b>	COVERAGE One litre of Reviva when diluted with 4 litres of water will treat approximately 5–10 square metres, subject to timber porosity, species and condition.		

Application Guide	
<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>Remove surface dirt by sweeping or washing down with water.</li> </ul>
<b>Application Procedure And Equipment</b>	<ul style="list-style-type: none"> <li>Shake Reviva thoroughly.</li> <li>Mix ONE (1) part Reviva to FOUR (4) parts water in a plastic container.</li> <li>For severe staining a stronger solution or repeat applications may be necessary. Tannin rich timbers may also require repeat applications; wash until the water used to rinse Reviva off is clear.</li> <li>CAUTION: Wear waterproof gloves and safety glasses. Avoid contact with painted, concrete or metal surfaces and vegetation. May be corrosive to metals. Rinse off thoroughly if contact occurs.</li> <li>Wet the timber surfaces to be cleaned with water.</li> <li>Apply Reviva mixture generously to the timber with a stiff bristle brush, broom or scouring pad. Scrub the timber vigorously. Clean complete sections at one time. Spot cleaning should be avoided to prevent patchy results.</li> <li>Leave mixture on the timber for 10-15 minutes. If necessary, apply more mixture to keep timber damp throughout this period. For best results Reviva should be applied to cool surfaces, out of direct sunlight, to avoid the cleaner drying on the timber.</li> <li>Rinse off exterior surfaces thoroughly using maximum pressure from a garden hose or using a high pressure water cleaner. A high pressure water cleaner is recommended for large areas or badly discoloured timber.</li> <li>Note: Failure to thoroughly remove mixture may result in timber discolouration under clear finishes.</li> <li>Allow timber to dry thoroughly before applying further products.</li> <li>Note: After cleaning, some timber species will appear lighter due to loss of water soluble extractives. Richer colour is generally restored on application of the finish.</li> </ul>

Health And Safety			
<b>MSDS Number</b>	3391	<b>Using Safety Precautions</b>	<p>RISK: Causes burns. Risk of serious damage to eyes. Avoid contact with skin and eyes.</p> <p>Wear overalls, rubber boots, impervious gloves, apron and full face shield. Use only in well ventilated areas. If inhalation risk exists wear acid mist respirator. Wash hands thoroughly after use. Store in a cool place and out of direct sunlight. Store away from oxidising agents. Keep containers closed when not in use. Do not empty into drains.</p>
<b>Health Effects</b>	<p>FIRST AID: If poisoning occurs, contact a Doctor or Poisons Information Centre (AUST: 131 126; NZ 0800 764 766).</p> <p>SWALLOWED: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.</p> <p>EYE: If in eyes, hold eyes open, flush with running water for at least 15 minutes and see a doctor.</p> <p>SKIN: If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.</p> <p>INHALED: Remove from contaminated area – avoid becoming a casualty. Keep at rest until fully recovered. Seek medical advice.</p> <p>EMERGENCY INFORMATION (ALL HOURS): AUST – 1800 033 111; NZ – 0800 734 607.</p> <p>INTERGRAIN CUSTOMER SERVICE: For further product or application advice or a Safety Data Sheet contact Intergrain Customer Service: Aust – 1800 630 285, NZ – 0800 222 687.</p> <p>*NEW ZEALAND: Products not available in New Zealand.</p>	<b>Flammability</b>	This product is non-flammable.
<b>Fire Suppression</b>	Non-combustible, however, if involved in a fire use water fog, foam or dry agents.	<b>Protective Equipment</b>	Wear overalls, rubber boots, impervious gloves, apron and full face shield.
<b>Storage</b>	<p>Keep out of reach of children.</p> <p>Keep containers closed when not in use.</p> <p>Store in a cool place and out of direct sunlight.</p> <p>Store away from oxidising agents.</p>	<b>Disposal</b>	Refer to Local Council or State/Territory Land Waste Management Authority for disposal. Small amounts may be disposed of with household garbage.
<b>Other</b>	POISON		
<b>In the case of emergency, please call 1800 033 111</b>			

Transport And Storage			
<b>Pack A</b>	552 94814	<b>Shipment Name</b>	CORROSIVE LIQUID
<b>Size</b>	10L 4L 1L	<b>Weight</b>	11.0kg 4.4kg 1.1kg
<b>UN Number</b>	3265	<b>Dangerous Goods Class</b>	8 Corrosive

**Disclaimer**

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427