



Toby Tung Oil Seal

AUDW1162

Part A	702 72300
---------------	-----------

Description

TOBY TUNG OIL SEAL is based on natural tung oil and provides interior timber, parquetry and cork floors with a natural oiled appearance.

Features

Based on natural tung oil.

Benefits

Gives a natural oiled appearance.

Uses




Use Toby Tung oil on interior timber, parquetry and cork flooring.

Precautions And Limitations

Do not apply if temperature is less than 10°C.
It is not recommended to apply TOBY TUNG OIL SEAL when the temperature exceeds 35°C or when the relative humidity exceeds 85%.

Performance Guide

Weather	For interior use only.	Salt	Unaffected by splash or spillage.
Heat Resistance	Up to 90°C. Yellowing and embrittlement will occur if subjected to continuous heat.	Water	Good resistance except to continuous immersion (ponding).
Solvent	Resists splashes of alcohols and hydrocarbons.	Abrasion	Moderate.
Acid	Suitable for splash.	Alkali	Suitable for splash.

Typical Properties																											
Colour	Clear	Components	1																								
Number Of Coats	2	Toxicity	Lead free.																								
V.O.C. Level	< 405g/L	Touch Dry	8 hours																								
Clean Up Description	Mineral turpentine. To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.																										
Application Method	 Brush  Roller  Pad																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Solids By Volume</td> <td style="text-align: center;">23</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">83</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">19</td> </tr> <tr> <td>Recoat Time (min)</td> <td style="text-align: center;">12 hours</td> <td></td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td></td> <td style="text-align: center;">12</td> <td style="text-align: center;">12</td> </tr> </table>			Solids By Volume	23				Min	Max	Recommended	Wet Film Per Coat (microns)			83	Dry Film Per Coat (microns)			19	Recoat Time (min)	12 hours			Theoretical Spread Rate (m²/L)		12	12
Solids By Volume	23																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			83																								
Dry Film Per Coat (microns)			19																								
Recoat Time (min)	12 hours																										
Theoretical Spread Rate (m²/L)		12	12																								
Typical Properties Notes	<p>COVERAGE 10-12 square metres per litre depending on the porosity of the timber.</p> <p>DRYING AND RECOAT TIME All timings quoted at 25C and 50% relative humidity. Drying times will be subject to climatic conditions, film thickness and airflow.</p> <p>Light foot traffic may be possible after 24 hours and normal traffic after 72 hours. Full cure after 14 days</p>																										

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> All surfaces must be clean, dry, free of wax, grease, dust and other contaminants. The presence of contaminants contributes to conditions such as 'rejection' or 'delamination'. If uneven, the surface should be sanded with coarse sandpaper. All nail-holes and cracks should be filled with a water based putty. Do not use Linseed Oil Putty. Fine sand the floor, finishing with 100-grit sandpaper, then with 120-mesh screenback and vacuum thoroughly with a commercial grade vacuum cleaner. If the surface has been previously coated ensure that it is thoroughly sanded to remove old coating.
Application Procedure And Equipment	<ul style="list-style-type: none"> Bare Timber Apply one sealer coat of TOBY RAPID-SEAL following instructions on the label. Sand the sealer coat with a worn 150-mesh screen if needed. Apply two coats of TOBY TUNG OIL SEAL with a soft bristle brush (edges), 6mm mohair roller or lambswool applicator. Lightly sand between the coats with a 220 screen or maroon pad if required. The more coats applied, the glossier the finish will become. Recoating Always perform a test patch after the floor is prepared to ensure adhesion. As is the case for new floors, the surface must be free of wax, grease, dust and other contaminants. Wash floors with INTERGRAIN ENVIROPRO SQUEAKY CLEAN. Sand surface to a dull matt finish using 100-mesh screenback then vacuum thoroughly and tack clean with a damp rag. Apply 1-2 coats of TOBY TUNG OIL SEAL as per application instructions.



Health And Safety			
MSDS Number	20162	Using Safety Precautions	RISK: Irritating to skin. Wear overalls, impervious gloves and safety glasses. Use only in well ventilated areas. If inhalation risk exists wear organic vapour/particulate respirator. Keep away from sources of ignition - No smoking. Keep containers closed when not in use.
Health Effects	FIRST AID: For advice, contact a Poisons Information Centre (Phone Australia 13 1126; New Zealand 0 800 764766) or a doctor. SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance. EYE: Rinse with plenty of running water. Seek medical help if irritation occurs. SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. INHALED: Remove from contaminated area.	Flammability	This product is flammable
Protective Equipment	Wear gloves, safety glasses and protective clothing.	Storage	Keep out of reach of children.
Disposal	Do not pour leftover product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collections. Empty product containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty product containers via domestic recycling programs may differ between local authorities. Check with your local council first.		
In the case of emergency, please call 1800 033 111			

Transport And Storage			
Pack A	702 72300	Shipment Name	PAINTS,
Size	4L 10 L 20L	Weight	4.5Kg 10.6 kg, 19.8Kg
Flash Point	>23C	UN Number	1263
Dangerous Goods Class	3	Package Group	III

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427