



Toby Aquamax Roller Seal

AUDW1203

Part A	701 72403
---------------	-----------

Description

Toby Aquamax Roller Seal is a water based sealer for timber floors. It seals all timber surfaces and provides a perfectly prepared surface for the application of Toby Aquamax water based timber floor finishes

Features

- Roller Applied
- Waterbased

Benefits

- More Productive
- Low Odour, Fast Clean Up

Uses




Interior timber floors.

Precautions And Limitations

Do not apply Toby Aquamax Roller Seal in temperatures below 10C or above 30C.

Performance Guide

Weather	Interior only.
----------------	----------------

Typical Properties																											
Colour	Clear	Components	1																								
Number Of Coats	1	V.O.C. Level	< 60g/L																								
Meets GBCA VOC Requirement?	Yes. Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.	Touch Dry	30 minutes																								
Clean Up	 Water																										
Clean Up Description	Water																										
Application Method	  Brush Roller																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: right;">Solids By Volume</td> <td style="text-align: center;">29</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td style="text-align: right;">Wet Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">100</td> </tr> <tr> <td style="text-align: right;">Dry Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">29</td> </tr> <tr> <td style="text-align: right;">Recoat Time (min)</td> <td style="text-align: center;">1 hour</td> <td></td> <td></td> </tr> <tr> <td style="text-align: right;">Theoretical Spread Rate (m²/L)</td> <td></td> <td style="text-align: center;">10</td> <td style="text-align: center;">10</td> </tr> </table>			Solids By Volume	29				Min	Max	Recommended	Wet Film Per Coat (microns)			100	Dry Film Per Coat (microns)			29	Recoat Time (min)	1 hour			Theoretical Spread Rate (m²/L)		10	10
Solids By Volume	29																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			100																								
Dry Film Per Coat (microns)			29																								
Recoat Time (min)	1 hour																										
Theoretical Spread Rate (m²/L)		10	10																								
Typical Properties Notes	<p>COVERAGE 8-10 square metres per litre depending on the porosity of the timber.</p> <p>DRYING AND RECOAT TIME All timings quoted at 25C and 50% relative humidity. Drying times will be subject to climatic conditions, film thickness and airflow.</p>																										

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> All surfaces must be clean, dry and free of wax, dust and other contaminants. All nail-holes and cracks should be filled with a water based putty. Do not use linseed oil putty. Fine sand the floor with 100 grit sandpaper and sand to a smooth surface with a 150 mesh screenback. If the surface has been previously coated, ensure that it is thoroughly sanded to remove old coating.
Application Procedure And Equipment	<ul style="list-style-type: none"> Apply one coat of Toby Aquamax Roller Seal using a 10mm nap roller. The product does not need to be sanded in order to achieve adhesion to the next coat. <p>Finishing Apply two coats of a Toby Aquamax water based finish as per label instructions.</p>



Health And Safety			
MSDS Number	20177	Using Safety Precautions	Irritating to eyes and may irritate skin. Potentially harmful if swallowed. Inhaling vapour may cause headache, dizziness and nausea. Avoid direct contact with skin.
Health Effects	<p>Further information on this product is available in the form of a Product Data Sheet or Material Safety Data Sheet from your local Orica Woodcare office or TOBY Distributor. If poisoning occurs, contact a doctor or Poisons Information Centre. Phone 13 11 26.</p> <p>SWALLOWED :Do NOT induce vomiting. Give a glass of water.</p> <p>EYES : Hold eyes open, flood with water for at least 15 minutes and see a doctor.</p> <p>SKIN : Remove contaminated clothing and wash skin thoroughly with soap and water.</p>	Flammability	This product is non-flammable.
Protective Equipment	Wear gloves, safety glasses and protective clothing.	Storage	Keep out of reach of Children.
Disposal	Do not pour leftover product down the drain. Keep unwanted product in sealed containers for disposal via special chemical waste collections. Disposal of empty containers via domestic kerbside recycling programs may differ between local authorities. Check with your local council first.		
In the case of emergency, please call 1800 033 111			

Transport And Storage	
Pack A	70172403
Size 5L	Weight 5.8Kg

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427