



DATA SHEET

Toby Aquamax Roller Seal

PRODUCT CODE 70172403

Data Sheet No. AUDW1203

APPROVALS

Description

TOBY AQUAMAX ROLLER SEAL is an environmentally safe, water-based sealer for timber. It seals all timber surfaces and provides a perfectly prepared surface for the application of all TOBY AQUAMAX timber floor finishes. TOBY AQUAMAX ROLLER SEAL can be applied by roller and it reduces the occurrence of shadow marks on the timber floors that are normally a problem with water-based timber floor coatings.

Features

Roller Applied
Waterbased

Benefits

More Productive
Low Odour, Fast Clean Up

Uses

Interior timber floors

Performance Guide

Weather	Interior Only	Salt	Good
Heat	up to 60 C	Solvent	Good for weak solutions
Abrasion	Good	Acid	Good for weak solutions
Alkali	Good for weak solutions		

Typical Properties and Application Data

Gloss Level	0	Spread Rate	8.9 sqm/L
Volume Solids	31.0	Components	1
Colour	Milkish White Liquid, drying to a clear finish	Toxicity	non-toxic
Number of Coats	1	Shelf life	12 months (in unopened container)
V.O.C Level	< 60g/L	Sanding Properties	Fair
Wet film per coat	Recommended 113 µm		
Dry film per coat	Recommended 35 µm	Touch Dry	30 - 45 min
Recoat	60 - 90 min		

Application Method



Application Guide

Surface Preparation

All surfaces must be clean, dry and free of wax, dust and other contaminants. The floor should be sanded with coarse sandpaper. All nail holes and cracks should be filled with putty. Fine sand the floor with 100 or 120-grit sandpaper and finish with a 150 mesh screenback. Vacuum thoroughly.

APPLICATION

Use a paint pad or polyester brush for the edges. Edge out 15 cm from the baseboard and keep a wet edge at all times. Apply product with 9 mm-nap roller finishing in the direction of the boards. Allow approximately 60 - 90 minutes to dry and sand with a worn 150 screen. The product does not need to be sanded in order to achieve adhesion to the next coat, however we recommend sanding because of the better finish that can be achieved.

Data Sheet	Toby Aquamax Roller Seal		
DuSpec Data Code	AUDW1203	Page No	1 of 3
Issue No	4.0	Date Issued	14/12/2011



DATA SHEET

Toby Aquamax Roller Seal

Data Sheet No. AUDW1203

Health and Safety

MSDS Number	20177	Using Safety Precautions	Irritating to eyes and may irritate skin. Potentially harmful if swallowed. Inhaling vapour may cause headache, dizziness and nausea. Avoid direct contact with skin.
Storage	Protect from extremes of temperature and frost, store between 5 - 30 C	Disposal	For large quantities refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by approved agent. For small quantities: Do not pour leftover material down drain. Unwanted material should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

In the case of emergency please call 1800 033 111

Precautions and Limitations

In high temperatures, add up to 5% Toby Aquamax Wet Edge Extender.

Drying time will be influenced by film thickness, temperature, humidity and airflow.

Do not apply if surface and/or air temperature is 10 degrees Celsius or lower, or is likely to fall below that during the drying period.

Transport and Storage

Pack A	70172403	Flash point	NA
Sizes	5L	UN Number	NA
Weight	5.8Kg	Package Group	NA
Dangerous Goods Class	nonflam		
Shipment Name	Waterbased		

Data Sheet	Toby Aquamax Roller Seal		
DuSpec Data Code	AUDW1203	Page No	2 of 3
Issue No	4.0	Date Issued	14/12/2011



DATA SHEET

Toby Aquamax Roller Seal

Data Sheet No. AUDW1203

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427

Data Sheet	Toby Aquamax Roller Seal		
DuSpec Data Code	AUDW1203	Page No	3 of 3
Issue No	4.0	Date Issued	14/12/2011