



## DATA SHEET

## Toby Rapid Seal

PRODUCT CODE 70372949

Data Sheet No. AUDW1206

## APPROVALS

## Description

Toby-Rapid seal dries quickly to enable fast recoating and has excellent adhesion to most Australian Timbers. It causes no significant darkening of timbers, and can be recoated with any Toby floor finish.

## Features

Roller Applied  
Solvent Based  
Special resins

## Benefits

More Productive  
Excellent adhesion properties  
Fast dry & re-coat. Will not darken timber

## Uses

Interior timber, parquetry and cork floors

## Performance Guide

<b>Weather</b>	Interior Only	<b>Salt</b>	NA
<b>Heat</b>	NA	<b>Water</b>	NA
<b>Solvent</b>	NA	<b>Abrasion</b>	Not designed as a topcoat.
<b>Acid</b>	NA	<b>Alkali</b>	NA

## Typical Properties and Application Data

<b>Gloss Level</b>	0	<b>Spread Rate</b>	11.0 sqm/L
<b>Volume Solids</b>	5.82	<b>Components</b>	1
<b>Colour</b>	Clear	<b>Number of Coats</b>	1
<b>V.O.C Level</b>	< 800g/L	<b>Wet film per coat</b>	Recommended 91 µm
<b>Touch Dry</b>	15 min	<b>Dry film per coat</b>	Recommended 5 µm
<b>Clean Up</b>	Feast Watson Super Solvent	<b>Recoat</b>	1 hour



## Application Method



## Application Guide

## Surface Preparation

All surfaces must be clean, dry and free of wax, dust and other contaminants. The floor should be sanded with coarse sandpaper. All nail holes and cracks should be filled with putty. Fine sand the floor with 100 or 120-grit sandpaper and close the grain with a 150 mesh screenback. If the surface has been previously coated ensure that it is thoroughly sanded to remove old coating.

## APPLICATION

Apply 1 coat of Rapid Seal by roller, brush or applicator at an application rate of 10-12m<sup>2</sup> per litre.

Data Sheet	Toby Rapid Seal		
DuSpec Data Code	AUDW1206	Page No	1 of 3
Issue No	6.0	Date Issued	14/12/2011

## DATA SHEET

### Toby Rapid Seal

Data Sheet No. AUDW1206

#### Health and Safety

**MSDS Number** 20161

**Using Safety Precautions** Do not use in the presence of naked flame or electrical appliances, and do not smoke while using. Provide adequate ventilation during application or wear suitable respiratory equipment. Avoid breathing the vapour as it may cause an asthma-like reaction. Repeated over exposure may cause sensitisation. Avoid contact with skin and eyes. Wear eye protection and solvent-resistant gloves when mixing or using this material.

**Health Effects** Irritating to skin. Danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. May cause lung damage if swallowed.

**Flammability** This product is flammable.

**Protective Equipment** Wear overalls, impervious gloves and chemical goggles. If inhalation risk exists wear organic vapour/particulate respirator

**Storage** Protect from extremes of temperature and frost, store between 5 - 30 C

**Disposal** For large quantities refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by approved agent. For small quantities: Do not pour leftover material down drain. Unwanted material should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

**In the case of emergency please call 1800 033 111**

#### Precautions and Limitations

Use below 10°C is not advised.  
It is not advised to apply coatings when the temperature exceeds 35°C as they may dry too quickly under the roller, resulting in a substandard finish.  
The drying time will vary greatly when the temperature is below 10°C or above 30°C or if the relative humidity is higher than 50%.

#### Transport and Storage

**Pack A** 70372949

**Sizes** 20L

**Weight** 19.8Kg

**Dangerous Goods Class** 3

**Shipment Name** PAINT

**Flash point** 4 C

**UN Number** 1263

**Package Group** II



## DATA SHEET

### Toby Rapid Seal

Data Sheet No. AUDW1206

#### Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427

Data Sheet	Toby Rapid Seal		
DuSpec Data Code	AUDW1206	Page No	3 of 3
Issue No	6.0	Date Issued	14/12/2011