

## Toby Rapid Seal

AUDW1206

Part A	703 72949
--------	-----------

### Description

TOBY® RAPID-SEAL is a rapid-drying sealer for timber and parquet floors.

### Features

- Roller Applied
- Solvent Based
- Special resins

### Benefits

- More Productive
- Excellent adhesion properties
- Fast dry & re-coat. Will not darken timber

### Uses

Interior timber, parquetry and cork floors

### Precautions And Limitations

Do not apply product if temperature is below 10°C or above 35°C. Relative humidity should not exceed 85%.

### Performance Guide

Weather	Interior Only
---------	---------------

### Typical Properties

Colour	Clear	Components	1																								
Number Of Coats	1	V.O.C. Level	< 760g/L																								
Touch Dry	15 minutes																										
Clean Up Description	Feast Watson Super Solvent. To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.																										
Application Method	 Brush  Roller																										
Application Conditions	<table border="1"> <thead> <tr> <th colspan="2">Solids By Volume</th> <th>5</th> <th></th> </tr> <tr> <th></th> <th>Min</th> <th>Max</th> <th>Recommended</th> </tr> </thead> <tbody> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td>100</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td>5</td> </tr> <tr> <td>Recoat Time (min)</td> <td>1 hour</td> <td></td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m<sup>2</sup>/L)</td> <td>10</td> <td>12</td> <td>10</td> </tr> </tbody> </table>	Solids By Volume		5			Min	Max	Recommended	Wet Film Per Coat (microns)			100	Dry Film Per Coat (microns)			5	Recoat Time (min)	1 hour			Theoretical Spread Rate (m <sup>2</sup> /L)	10	12	10		
Solids By Volume		5																									
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			100																								
Dry Film Per Coat (microns)			5																								
Recoat Time (min)	1 hour																										
Theoretical Spread Rate (m <sup>2</sup> /L)	10	12	10																								
Typical Properties Notes	<p>COVERAGE 10-12 square metres per litre depending on the porosity of the timber.</p> <p>DRYING AND RECOAT TIME All timings quoted at 25C and 50% relative humidity. Drying times will be subject to climatic conditions, film thickness and airflow.</p>																										



Application Guide	
<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>All surfaces must be clean, dry, free of wax, grease, dust and other contaminants. The presence of contaminants contributes to conditions such as 'rejection' or 'delamination'. If uneven, the surface should be sanded with coarse sandpaper. All nail-holes and cracks should be filled with a water based putty. Do not use linseed oil putty. Fine sand the floor, finishing with 100-grit sandpaper, then with 120-mesh screenback and vacuum thoroughly with a commercial grade vacuum cleaner. If the surface has been previously coated ensure that it is thoroughly sanded to remove old coating.</li> </ul>
<b>Application Procedure And Equipment</b>	<ul style="list-style-type: none"> <li>Apply one coat of TOBY RAPID SEAL by brush or with a 6mm mohair roller. If sanding of the sealer is required use a worn 150-mesh screen.</li> </ul>

Health And Safety			
<b>MSDS Number</b>	20161	<b>Using Safety Precautions</b>	Highly Flammable. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Harmful to aquatic organisms. May cause long term adverse effects in the aquatic environment. Possible risk of harm to the unborn child. May cause harm to breastfed babies. Harmful: May cause lung damage if swallowed. Avoid contact with skin and eyes and breathing in vapour or spray mist. Wear overalls, impervious gloves and chemical goggles. Use only in well ventilated areas. If inhalation risk exists wear organic vapour/particulate respirator. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Do not empty into drains. Keep containers closed when not in use.
<b>Health Effects</b>	<p>FIRST AID: For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.</p> <p>SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance.</p> <p>EYE: Rinse with plenty of running water. Seek medical help if irritation occurs.</p> <p>SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.</p> <p>INHALED: Remove from contaminated area.</p>	<b>Flammability</b>	This product is highly flammable.
<b>Protective Equipment</b>	Wear gloves, safety glasses and protective clothing.	<b>Storage</b>	Keep out of reach of children.
<b>Disposal</b>	Do not pour leftover product down the drain. Keep unwanted product in sealed containers for disposal via special chemical waste collections. Disposal of empty containers via domestic kerbside recycling programs may differ between local authorities. Check with your local council first.		
<b>In the case of emergency, please call 1800 033 111</b>			

Transport And Storage			
<b>Pack A</b>	70372949	<b>Shipment Name</b>	PAINT
<b>Size</b>	20L	<b>Weight</b>	19.8Kg
<b>Flash Point</b>	4C	<b>UN Number</b>	1263
<b>Dangerous Goods Class</b>	3	<b>Package Group</b>	I



**Disclaimer**

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427