

## DATA SHEET

## Toby GF Barrier Seal

PRODUCT CODE 70372030

Data Sheet No. AUDW1208

## APPROVALS

## Description

Toby GF Barrier Seal can be used as a fast drying sealer for strip timber and parquetry. It offers outstanding grain filling properties and excellent barrier properties. The product can reduce the occurrence of rejection on the old timber floors that are recoated with solvent-based Toby timber finishes.

## Features

Roller Applied  
Solvent Based  
Excellent barrier properties  
Outstanding grain filling properties

## Benefits

Very easy application  
Excellent adhesion properties  
Reduces incidences of 'rejection"  
Reduces surface porosity

## Uses

Strip timber and parquetry floors

## Performance Guide

<b>Weather</b>	Interior Only	<b>Salt</b>	NA
<b>Heat</b>	60 C	<b>Water</b>	NA
<b>Solvent</b>	NA	<b>Abrasion</b>	NA
<b>Acid</b>	NA	<b>Alkali</b>	NA

## Typical Properties and Application Data


<b>Gloss Level</b>	0	<b>Spread Rate</b>	8.0 sqm/L
<b>Volume Solids</b>	16.0	<b>Components</b>	1
<b>Colour</b>	Slightly hazy liquid	<b>Toxicity</b>	Toxic
<b>Number of Coats</b>	1	<b>Shelf life</b>	12 months (in unopened container)
<b>V.O.C Level</b>	< 685g/L	<b>Sanding Properties</b>	Good
<b>Wet film per coat</b>	Recommended 125 µm	<b>Touch Dry</b>	30 min
<b>Dry film per coat</b>	Recommended 20 µm	<b>Clean Up</b>	Feast Watson Super Solvent
<b>Recoat</b>	1.5 Hrs		



## Application Method



Data Sheet	Toby GF Barrier Seal		
DuSpec Data Code	AUDW1208	Page No	1 of 3
Issue No	4.0	Date Issued	09/08/2010



## DATA SHEET

### Toby GF Barrier Seal

**Data Sheet No.** AUDW1208

#### Application Guide

##### Surface Preparation

All surfaces must be clean, dry and free of wax, dust and other contaminants. The floor should be sanded with coarse sandpaper. Ensure the surface is thoroughly vacuumed with a commercial grade vacuum cleaner.

##### Notes

NOTE: Toby GF Barrier Seal has excellent barrier properties and helps to prevent the topcoat from rejecting. However, it is always recommended to properly clean the floor prior to any sealer because some forms of contaminants may still be on the sealer surface after drying and may cause the finish coat to reject or delaminate.

#### Health and Safety

**MSDS Number** 20160

**Using Safety Precautions** This material is **FLAMMABLE**. Do not use in the presence of naked flame or electrical appliances, and do not smoke while using. Provide adequate ventilation during application or wear suitable respiratory equipment. Avoid breathing the vapour as it may cause an asthma-like reaction. Repeated over exposure may cause sensitisation. Avoid contact with skin and eyes. Wear eye protection and solvent-resistant gloves when mixing or using this material.

**Flammability** Yes

**Storage** Protect from extremes of temperature and frost, store between 12 - 30 C

**Disposal** For large quantities refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by approved agent. For small quantities: Do not pour leftover material down drain. Unwanted material should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

**In the case of emergency please call 1800 033 111**

#### Precautions and Limitations

#### Transport and Storage

**Pack A** 70372030

**Sizes** 20Kg

**Weight** 19.7Kg

**Dangerous Goods Class** Flammable

**Shipment Name** Solvent Based

**Flash point** -7 C

**UN Number** 1263

**Package Group** III

<b>Data Sheet</b>	Toby GF Barrier Seal		
<b>DuSpec Data Code</b>	AUDW1208	<b>Page No</b>	2 of 3
<b>Issue No</b>	4.0	<b>Date Issued</b>	09/08/2010



## DATA SHEET

### Toby GF Barrier Seal

Data Sheet No. AUDW1208

#### Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427

Data Sheet	Toby GF Barrier Seal		
DuSpec Data Code	AUDW1208	Page No	3 of 3
Issue No	4.0	Date Issued	09/08/2010