

DATA SHEET

Toby GF Barrier Seal

PRODUCT CODE 70372030

Data Sheet No. AUDW1208

APPROVALS

Description

Toby GF Barrier Seal can be used as a fast drying sealer for strip timber and parquetry. It offers outstanding grain filling properties and excellent barrier properties. The product can reduce the occurrence of rejection on the old timber floors that are recoated with solvent-based Toby timber finishes.

Features

Roller Applied
Solvent Based
Excellent barrier properties
Outstanding grain filling properties

Benefits

Very easy application
Excellent adhesion properties
Reduces incidences of 'rejection"
Reduces surface porosity

Uses

Strip timber and parquetry floors

Performance Guide

Weather	Interior Only	Salt	NA
Heat	60 C	Water	NA
Solvent	NA	Abrasion	NA
Acid	NA	Alkali	NA

Typical Properties and Application Data

Gloss Level	0	Spread Rate	8.0 sqm/L
Volume Solids	16.0	Components	1
Colour	Slightly hazy liquid	Toxicity	Toxic
Number of Coats	1	Shelf life	12 months (in unopened container)
V.O.C Level	< 685g/L	Sanding Properties	Good
Wet film per coat	Recommended 125 µm	Touch Dry	30 min
Dry film per coat	Recommended 20 µm	Clean Up	Feast Watson Super Solvent
Recoat	1.5 Hrs		



Application Method



Data Sheet	Toby GF Barrier Seal		
DuSpec Data Code	AUDW1208	Page No	1 of 3
Issue No	4.0	Date Issued	14/12/2011

DATA SHEET

Toby GF Barrier Seal

	Data Sheet No. AUDW1208
--	--------------------------------

Application Guide

Surface Preparation

All surfaces must be clean, dry and free of wax, dust and other contaminants. The floor should be sanded with coarse sandpaper. Ensure the surface is thoroughly vacuumed with a commercial grade vacuum cleaner.

Notes

NOTE: Toby GF Barrier Seal has excellent barrier properties and helps to prevent the topcoat from rejecting. However, it is always recommended to properly clean the floor prior to any sealer because some forms of contaminants may still be on the sealer surface after drying and may cause the finish coat to reject or delaminate.

Health and Safety

MSDS Number	20160	Using Safety Precautions	This material is FLAMMABLE . Do not use in the presence of naked flame or electrical appliances, and do not smoke while using. Provide adequate ventilation during application or wear suitable respiratory equipment. Avoid breathing the vapour as it may cause an asthma-like reaction. Repeated over exposure may cause sensitisation. Avoid contact with skin and eyes. Wear eye protection and solvent-resistant gloves when mixing or using this material.
Flammability	Yes	Storage	Protect from extremes of temperature and frost, store between 12 - 30 C
Disposal	For large quantities refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by approved agent. For small quantities: Do not pour leftover material down drain. Unwanted material should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.		

In the case of emergency please call 1800 033 111

Precautions and Limitations

Transport and Storage

Pack A	70372030	Flash point	-7 C
Sizes	20Kg	UN Number	1263
Weight	19.7Kg	Package Group	III
Dangerous Goods Class	Flammable		
Shipment Name	Solvent Based		



DATA SHEET

Toby GF Barrier Seal

Data Sheet No. AUDW1208

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427

Data Sheet	Toby GF Barrier Seal		
DuSpec Data Code	AUDW1208	Page No	3 of 3
Issue No	4.0	Date Issued	14/12/2011