

## Toby GF Barrier Seal

AUDW1208

Part A	703 72030
--------	-----------

### Description

TOBY® GF BARRIER SEAL is a fast drying sealer for timber and parquetry floors. It offers outstanding grain filling and barrier properties. The product can reduce the occurrence of rejection and tannin bleed on oily and tannin rich timbers. It also has excellent colour development.

### Features

- Roller Applied
- Solvent Based
- Excellent barrier properties
- Outstanding grain filling properties

### Benefits

- Very easy application
- Excellent adhesion properties
- Reduces incidences of "rejection"
- Reduces surface porosity

### Uses

Strip timber and parquetry floors.



### Precautions And Limitations

Do not apply product if temperature is below 10°C or above 35°C. Relative humidity should not exceed 85%.

### Performance Guide

Weather	Interior Only
---------	---------------

### Typical Properties

Colour	Clear	Components	1																				
Number Of Coats	1	V.O.C. Level	< 685g/L																				
Shelf Life	12 months (in unopened container)	Touch Dry	30 minutes																				
Clean Up Description	Feast Watson Super Solvent. To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.																						
Application Method	 Brush  Roller																						
Application Conditions	<p><b>Solids By Volume</b> 15</p> <table border="1"> <thead> <tr> <th></th> <th>Min</th> <th>Max</th> <th>Recommended</th> </tr> </thead> <tbody> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td>80</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td>13</td> </tr> <tr> <td>Recoat Time (min)</td> <td>1.5 hours</td> <td></td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m<sup>2</sup>/L)</td> <td></td> <td>12</td> <td>12</td> </tr> </tbody> </table>		Min	Max	Recommended	Wet Film Per Coat (microns)			80	Dry Film Per Coat (microns)			13	Recoat Time (min)	1.5 hours			Theoretical Spread Rate (m <sup>2</sup> /L)		12	12		
	Min	Max	Recommended																				
Wet Film Per Coat (microns)			80																				
Dry Film Per Coat (microns)			13																				
Recoat Time (min)	1.5 hours																						
Theoretical Spread Rate (m <sup>2</sup> /L)		12	12																				
Typical Properties Notes	<p>COVERAGE 10-12 square metres per litre depending on the porosity of the timber.</p> <p>DRYING AND RECOAT TIME All timings quoted at 25C and 50% relative humidity. Drying times will be subject to climatic conditions, film thickness and airflow.</p>																						



Application Guide	
<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>All surfaces must be clean, dry, free of wax, grease, dust and other contaminants. The presence of contaminants contributes to conditions such as 'rejection' or 'delamination'. If uneven, the surface should be sanded with coarse sandpaper. All nailholes and cracks should be filled with a water based putty. Do not use linseed oil putty. Fine sand the floor, finishing with 100-grit sandpaper, then with 120-mesh screenback and vacuum thoroughly with a commercial grade vacuum cleaner. If the surface has been previously coated ensure that it is thoroughly sanded to remove old coating.</li> </ul>
<b>Application Procedure And Equipment</b>	<ul style="list-style-type: none"> <li>Apply one coat of TOBY® GF BARRIER SEAL by brush or with a 6mm mohair roller. If sanding of the sealer is required use a 150-180 mesh screenback.</li> <li>Finishing</li> <li>Apply two coats of the TOBY solvent or water based finish as per instructions.</li> </ul>

Health And Safety			
<b>MSDS Number</b>	20160	<b>Using Safety Precautions</b>	<p>RISK: Highly Flammable. Harmful by inhalation, in contact with skin and if swallowed. Irritating to skin. Risk of serious damage to eyes.</p> <p>Avoid contact with skin and eyes and breathing in vapour or spray mist. Use only in well ventilated areas. Wear overalls, impervious gloves and chemical goggles. If inhalation risk exists wear organic vapour/particulate respirator. This paint is flammable, so eliminate any sources of ignition. Do not smoke. Do not empty into drains. Keep containers closed when not in use.</p>
<b>Health Effects</b>	<p>FIRST AID: For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.</p> <p>Swallowed: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance.</p> <p>Eye: If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.</p> <p>Skin: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.</p> <p>Inhaled: Remove from contaminated area.</p>	<b>Flammability</b>	This product is highly flammable.
<b>Protective Equipment</b>	Wear gloves, safety glasses and protective clothing.	<b>Storage</b>	Keep out of reach of children.
<b>Disposal</b>	Do not pour leftover product down the drain. Keep unwanted product in sealed containers for disposal via special chemical waste collections. Disposal of empty containers via domestic kerbside recycling programs may differ between local authorities. Check with your local council first.		
<b>In the case of emergency, please call 1800 033 111</b>			

Transport And Storage			
<b>Pack A</b>	70372030	<b>Shipment Name</b>	PAINT
<b>Size</b>	20Kg	<b>Weight</b>	19.7Kg
<b>Flash Point</b>	13C	<b>UN Number</b>	1263
<b>Dangerous Goods Class</b>	3	<b>Package Group</b>	I



**Disclaimer**

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427