



**DATA SHEET**

**Toby Lustapol**

**PRODUCT CODE PART A** 70372201 **PART B** 70372208 **Data Sheet No. AUDW1213**

**APPROVALS**

**Description**

Toby Lustapol is a premium two-pack polyurethane timber finish for parquetry and timber surfaces designed for use by tradesman and professional applicators. It resists expansion, flexing, indentation and withstands fracture. Lustapol provides a clear, smooth, high gloss finish with excellent resistance to abrasion and chemicals.

**Features**

2 pack mix  
Chemical dry

**Benefits**

very tough finish  
More reliable dry in cold conditions


**Uses**

Timber & parquetry floors. Not recommended for cork floors.

**Performance Guide**

<b>Weather</b>	Interior Only	<b>Salt</b>	Excellent
<b>Heat</b>	60 C	<b>Water</b>	Excellent
<b>Solvent</b>	Excellent	<b>Abrasion</b>	Excellent
<b>Acid</b>	Excellent	<b>Alkali</b>	Excellent

**Typical Properties and Application Data**

<b>Gloss Level</b>	85-95 at 65 Degrees	<b>Thinner</b>	Feast Watson Reducer Thinners
<b>Gloss Level Ind</b>		<b>Spread Rate</b>	11.0 sqm/L
<b>Volume Solids</b>	46.0	<b>Components</b>	2
<b>Colour</b>	Pale straw coloured clear liquid	<b>Number of Coats</b>	3
<b>Shelf life</b>	12 months	<b>V.O.C Level</b>	< 430g/L
<b>Sanding Properties</b>	Good	<b>Mixing Ratio</b>	1:1
<b>Pot Life</b>	4 hrs once mixed	<b>Wet film per coat</b>	Recommended 91 µm
<b>Recoat</b>	8 hrs	<b>Dry film per coat</b>	Recommended 42 µm
		<b>Clean Up</b>	Feast Watson Super Solvent



**Application Method**



## DATA SHEET

### Toby Lustapol

**Data Sheet No. AUDW1213**

#### Application Guide

##### Surface Preparation

All surfaces must be clean, dry and free of wax, grease, dust and other contaminants. The presence of such contaminants contributes to conditions such as 'rejection' or 'delamination'. If uneven, the surface should be sanded with coarse sandpaper initially. All nail-holes and cracks should be filled with putty, Fine sand the floor, finishing with 100 grit sand paper, then with 100 mesh screen back and vacuum thoroughly.

##### APPLICATION

Apply a sealer coat of Toby Rapid Seal, prior to application of Lustapol.

Mix equal parts by volume of Lustapol Part A and Part B. Use a graduated measuring jug to ensure an accurate mix ratio.

Apply Lustapol with a soft bristle brush, lambswool applicator or mohair roller. Ensure the application is uniform. Allow first coat to dry for a minimum of 8 hours. Lightly sand with a 100 mesh screenback between coats. Thoroughly remove all sanding dust. Repeat application procedure for the final coat.

##### RECOATING

Sweep the floor to remove dirt, dust and loose particles. Clean the floor with a pH neutral floor cleaner to remove all traces of grease, grime, etc. Abrade the surface to a dull texture using a 100 grit screenback. Thoroughly remove all sanding dust. Apply one coat of Lustapol as above.

##### Notes

Toby Lustapol is manufactured to the correct consistency for application by soft bristle brush, lambswool applicator or mohair roller. However, if thickening has occurred due to ageing, thin with up to 10% with Feast Watson Reducer Thinners.

Complete curing of Lustapol takes approximately 7-10 days after application of the final coat, and care must be exercised during this period. Avoid moving chairs or furniture over the surface and use mats in high traffic areas.

To extend the life of the floor, use floor-glides under chair and furniture legs. Sweep the floor regularly and wash periodically with a pH neutral floor cleaner.

#### Health and Safety

<b>MSDS Number</b>	20151	<b>Flammability</b>	Flamable
<b>Personal</b>	Do not use if sensitised to isocyanates	<b>Protective Equipment</b>	Full mask with organic vapour cartridge
<b>Storage</b>	Toby Lustapol has a shelf life of at least 12 months, if stored in original, unopened containers, in clean, cool, dry conditions away from sources of heat and naked flames.	<b>Disposal</b>	For large quantities refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by approved agent. For small quantities: Do not pour leftover material down drain. Unwanted material should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

**In the case of emergency please call 1800 033 111**

#### Precautions and Limitations

<b>Data Sheet</b>	Toby Lustapol		
<b>DuSpec Data Code</b>	AUDW1213	<b>Page No</b>	2 of 3
<b>Issue No</b>	6.0	<b>Date Issued</b>	14/12/2011



## DATA SHEET

### Toby Lustapol

Data Sheet No. AUDW1213

#### Transport and Storage

<b>Pack A</b>	70372201		
<b>Sizes</b>	20 L	<b>Flash point</b>	23 C
<b>Weight</b>	19.4Kg	<b>UN Number</b>	1263
<b>Dangerous Goods Class</b>	flammable	<b>Package Group</b>	3
<b>Shipment Name</b>	Solvent Based		
<b>Pack B</b>	70372208		
<b>Sizes</b>	20L	<b>Flash point</b>	23 C
<b>Weight</b>	20.6Kg	<b>UN Number</b>	1263
<b>Dangerous Goods Class</b>	flammable	<b>Package Group</b>	3

#### Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427

Data Sheet	Toby Lustapol		
DuSpec Data Code	AUDW1213	Page No	3 of 3
Issue No	6.0	Date Issued	14/12/2011