



Toby Lustapol Gloss

AUDW1213

Part A	703 72201	Part B	703 72208
---------------	-----------	---------------	-----------

Description

DESCRIPTION: TOBY® LUSTAPOL® is a two pack polyurethane timber finish for timber and parquet floors. TOBY LUSTAPOL resists expansion, flexing, indentation and withstands fracture. TOBY LUSTAPOL provides, clear, smooth, high gloss finish with excellent resistance to abrasion and chemicals.

NOTE: TOBY LUSTAPOL is not recommended for use on cork floors.

Features

- 2 pack mix
- Chemical dry

Benefits

- very tough finish
- More reliable dry in cold conditions

Uses

Timber & parquet floors. Not recommended for cork floors.

Precautions And Limitations



DO NOT APPLY BY SPRAY.

Do not apply if temperature is less than 10°C.

It is not recommended to apply TOBY LUSTAPOL when the temperature exceeds 35°C or when the relative humidity exceeds 85%.

Performance Guide

Weather	Interior Only	Salt	Excellent
Heat Resistance	120C	Water	Excellent
Solvent	Excellent	Abrasion	Excellent
Acid	Excellent	Alkali	Excellent

Typical Properties																											
Gloss Level	Gloss	Thinner	Feast Watson Reducer Thinners																								
Colour	Clear	Components	2																								
Number Of Coats	2	V.O.C. Level	< 430g/L																								
Shelf Life	12 months	Mixing Ratio	1:1																								
Pot Life	4 hours	Touch Dry	4 hours																								
Clean Up Description	Feast Watson Super Solvent. To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.																										
Application Method	  Brush Roller																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Solids By Volume</td> <td style="text-align: center;">46</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">100</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">46</td> </tr> <tr> <td>Recoat Time (min)</td> <td style="text-align: center;">8 hours</td> <td></td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td></td> <td style="text-align: center;">10</td> <td style="text-align: center;">10</td> </tr> </table>			Solids By Volume	46				Min	Max	Recommended	Wet Film Per Coat (microns)			100	Dry Film Per Coat (microns)			46	Recoat Time (min)	8 hours			Theoretical Spread Rate (m²/L)		10	10
Solids By Volume	46																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			100																								
Dry Film Per Coat (microns)			46																								
Recoat Time (min)	8 hours																										
Theoretical Spread Rate (m²/L)		10	10																								
Typical Properties Notes	<p>COVERAGE 8-10 square metres per litre depending on the porosity of the timber.</p> <p>DRYING AND RECOAT TIME All timings quoted at 25C and 50% relative humidity. Drying times will be subject to climatic conditions, film thickness and airflow.</p> <p>Light foot traffic may be possible after 24 hours and normal traffic after 72 hours. Full cure after 14 days.</p>																										

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> All surfaces must be clean, dry, free of wax, grease, dust and other contaminants. The presence of contaminants contributes to conditions such as 'rejection' or 'delamination'. If uneven, the surface should be sanded with coarse sandpaper. All nail holes and cracks should be filled with a water based putty. Do not use linseed oil putty. Fine sand the floor, finishing with 100-grit sandpaper, then with 120-mesh screenback and vacuum thoroughly with a commercial grade vacuum cleaner. If the surface has been previously coated ensure that it is thoroughly sanded to remove old coating.
Application Procedure And Equipment	<ul style="list-style-type: none"> DO NOT APPLY BY SPRAY. <p>Bare Timber Apply one sealer coat of TOBY RAPID SEAL or TOBY GF BARRIER SEAL following instructions on the label. Sand the sealer coat with a worn 150-mesh screen if needed. Mix equal parts by volume of TOBY LUSTAPOL Part A and Part B before use. Use graduated measuring jugs to ensure accurate mix. Apply two coats of TOBY LUSTAPOL with a soft bristle brush (edges) and 6mm mohair roller. Screen between coats using a 120 mesh screen.</p> <p>Recoating Always perform a test patch after the floor is prepared to ensure adhesion. As is the case for new floors, the surface must be free of wax, grease, dust and other contaminants. Wash floors with INTERGRAIN ENVIROPRO SQUEAKY CLEAN. Sand surface to a dull matt finish using 100-mesh screenback then vacuum thoroughly and tack clean with a damp rag. Apply one coat of TOBY LUSTAPOL as per application instructions.</p> <p>Any residual sanding dust or airborne dust particles will cause pimples in the final film. For the final coat, sealing of doors, open fireplaces and windows is recommended to avoid any foreign material settling on surfaces.</p>



Health And Safety			
MSDS Number	20151 Toby Lustapol Part A 20158 Toby Lustapol Part B	Using Safety Precautions	Avoid contact with skin and eyes and breathing in vapour or spray mist. Wear overalls, impervious gloves and safety glasses. Use only in well ventilated areas. If inhalation risk exists wear organic vapour/ particulate respirator. Keep away from sources of heat or ignition - No smoking. Take precautionary measures against static discharges. Do not empty into drains. Keep containers closed when not in use.
Health Effects	FIRST AID: For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor. SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance. EYE: Irrigate with copious quantities of water. Seek medical assistance if effects persist. SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly. INHALED: Remove from contaminated area.	Flammability	This product is flammable.
Protective Equipment	Wear gloves, safety glasses and protective clothing.	Storage	Keep out of reach of children.
Disposal	Do not pour leftover product down the drain. Keep unwanted product in sealed containers for disposal via special chemical waste collections. Disposal of empty containers via domestic kerbside recycling programs may differ between local authorities. Check with your local council first.		
In the case of emergency, please call 1800 033 111			

Transport And Storage			
Pack A	70372201	Shipment Name	PAINT
Size	20 L	Weight	19.4Kg
Flash Point	>23C	UN Number	1263
Dangerous Goods Class	3	Package Group	III
Pack B	70372208	Shipment Name	PAINT
Size	20L	Weight	20.6Kg
Flash Point	>23C	UN Number	1263
Dangerous Goods Class	3	Package Group	III



Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427