

## Intergrain Ultragrip

AUDW1399

<b>Part A</b>	552 94992
---------------	-----------


<b>Description</b>
Intergrain UltraGrip is a slip resistant additive that has been specially formulated for use in various compatible* coatings. When used with these products, UltraGrip provides a high performance, long lasting finish which reduces the tendency for timber decking, exterior walkways, interior floors and stairs to become slippery.

<b>Features</b>
<ul style="list-style-type: none"> <li>Slip resistant additive</li> <li>Suitable for interior and exterior use</li> </ul>

<b>Benefits</b>
<ul style="list-style-type: none"> <li>Provides added slip resistance</li> <li>Wide range of applications</li> </ul>

<b>Precautions And Limitations</b>
Intergrain UltraGrip must only be added to compatible* coatings. When Intergrain UltraGrip is added, the gloss level of the resultant coating will be lower than normal.

<b>Performance Guide</b>	
<b>Weather</b>	Suitable for interior and exterior applications.

<b>Typical Properties</b>			
<b>V.O.C. Level</b>	0g/L	<b>Meets GBCA VOC Requirement?</b>	Yes. Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.
<b>Clean Up</b>	 Water		

**Application Guide**

**Application Procedure And Equipment**

- Intergrain UltraGrip must be added at a rate of 5%. That is:
  - 200g of UltraGrip for 4L of coating
  - 250g of UltraGrip for 5L of coating
  - 500g of UltraGrip for 10L of coating

\*Compatible coatings:

- Intergrain UltraDeck
- Intergrain NaturalStain
- Intergrain DWD
- Intergrain UltraFloor Satin
- Intergrain UltraFloor Pro Satin
- Enviropro Endure 1 Pack Satin
- Enviropro Endure 2 Pack Satin
- Enviropro Endure Deck
- Enviropro Endure Deck Stain
- Cabot's CFP Floor Water Based Satin
- Cabot's CFP Floor Oil Based Satin
- Feast Watson Matt Look Deck

Note: When UltraGrip is added, the sheen or gloss level of the resultant coating will be lower than normal.

For the coating systems required to achieve these slip ratings, please see individual product datasheets.

**SLIP RESISTANCE RATINGS**

Tested to AS4586-2013 Slip resistance classification of new pedestrian surface materials.

**Intergrain UltraDeck**

WET Pendulum = Class P4

OIL-WET Ramp = Slip Resistance Assessment Group R11

**Intergrain NaturalStain**

WET Pendulum = Class P4

OIL-WET Ramp = Slip Resistance Assessment Group R11

**Intergrain UltraFloor Satin**

WET Pendulum = Class P4 (UltraGrip in one coat of UltraFloor)

WET Pendulum = Class P5 (UltraGrip in two coats of UltraFloor)

**Intergrain UltraFloor Pro Satin**

WET Pendulum = Class P4 (UltraGrip in one coat of UltraFloor Pro)

WET Pendulum = Class P5 (UltraGrip in two coats coat of UltraFloor Pro)

**Enviropro Endure 1 Pack Satin**

WET Pendulum = Class P4 (UltraGrip in one coat of Endure)

WET Pendulum = Class P5 (UltraGrip in two coats of Endure)

**Enviropro Endure 2 Pack Satin**

WET Pendulum = Class P4 (UltraGrip in one coat of Endure)

WET Pendulum = Class P5 (UltraGrip in two coats coat of Endure)

**Enviropro Endure Deck**

WET Pendulum = Class P4

**Enviropro Endure Deck Stain**

WET Pendulum = Class P4

**Cabot's CFP Floor Water Based Satin**

WET Pendulum = Class P4 (UltraGrip in one coat of CFP Water Based)

**Cabot's CFP Floor Oil Based Satin**

WET Pendulum = Class P4 (UltraGrip in one coat of CFP Oil Based)

**Feast Watson Matt Look Deck**

WET Pendulum = Class P4

Tested to AS4586-2004 Slip resistance classification of new pedestrian surface materials.

**Intergrain DWD**

WET Pendulum = Class X

OIL-WET Ramp = Slip Resistance Assessment Group R10

Health And Safety			
<b>MSDS Number</b>	21728	<b>Using Safety Precautions</b>	Provide adequate ventilation. Wash hands after use.
<b>Health Effects</b>	<p>For detailed information refer to product label and the current Material Safety Data Sheet available through INTERGRAIN Sales and Customer Service offices.</p> <p>Avoid breathing in dust and contact with skin and eyes.</p> <p>FIRST AID: If poisoning occurs, contact a doctor or Poisons Information Centre. Phone 13 11 26.</p> <p>SWALLOWED: Give plenty of water to drink. Seek medical advice.</p> <p>EYE: Rinse with plenty of running water. Seek medical help if irritation occurs.</p>	<b>Flammability</b>	This product is non-flammable.
<b>Protective Equipment</b>	Wear eye protection, dust mask and gloves.	<b>Storage</b>	Keep out of reach of children.
<b>Disposal</b>	Normally suitable for disposal at approved waste land sites.		
<b>In the case of emergency, please call 1800 033 111</b>			

Transport And Storage	
<b>Pack A</b>	55294992
<b>Size</b>	<b>Weight</b>
200g	350g
500g	800g

**Disclaimer**

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427