

## Intergrain Enviropro 30+ Wet Edge Extender

**PRODUCT CODE** 701 94907

**Data Sheet No.** AUDW1436

**APPROVALS**

### Description

Intergrain Enviropro 30+ Wet Edge Extender is a high performance, environmentally responsible, water based wet edge extender for use with Enviropro Endure 1 Pack, Endure 2 Pack, Endure High Build and Timberseal. 30+ Wet Edge Extender is an additive that increases the working time of all Enviropro timber coatings without affecting the viscosity of the coating. It improves levelling, especially at higher temperatures and helps to reduce the occurrence of lap marking caused by the coating drying too quickly.

Being water based, 30+ Wet Edge Extender emits significantly less VOCs (volatile organic compounds) into the atmosphere than traditional solvent based finishes. So, combined with being safer to use, 30+ Wet Edge Extender is much gentler on the environment.

### Features

### Benefits

### Uses

Use in conditions where a longer wet edge time for any of the Enviropro products is required. Temperatures of 30°C and above, low humidity and high airflow rates and large areas present wet edge challenges.

### Performance Guide

**Weather** Interior use only.

### Typical Properties and Application Data

<b>Spread Rate</b>	0.0 sqm/L	<b>Components</b>	1
<b>Wet film per coat</b>	Recommended 0 µm		
<b>Dry film per coat</b>	Recommended 0 µm		

### Application Guide

#### Surface Preparation

Add 5% of 30+ Wet Edge Extender into the selected Enviropro product. Shake the mixture for 2 minutes to incorporate.

Note: 30+ Wet Edge Extender increases the drying time of the coating therefore, a longer time before overcoating will be required under certain conditions.

<b>Data Sheet</b>	Intergrain Enviropro 30+ Wet Edge Extender		
<b>DuSpec Data Code</b>	AUDW1436	<b>Page No</b>	1 of 2
<b>Issue No</b>	3.0	<b>Date Issued</b>	14/12/2011

## Intergrain Enviropro 30+ Wet Edge Extender

<b>Data Sheet No.</b>	AUDW1436
-----------------------	----------

### Health and Safety

<b>MSDS Number</b>	21042	<b>Using Safety Precautions</b>	Provide adequate ventilation. Keep windows and doors open during use and while drying.
<b>Health Effects</b>	FIRST AID: For advice, contact a Doctor or Poisons Information Centre. Phone 13 11 26. SWALLOWED: Give plenty of water to drink. Seek medical advice. EYE: Rinse with plenty of running water. Seek medical assistance if effects persist. SKIN: Wash contaminated skin with plenty of soap and water. If irritation occurs, seek medical advice. INHALED: Remove from contaminated area.	<b>Flammability</b>	This product is non-flammable.
<b>Protective Equipment</b>	Wear gloves, safety glasses and protective clothing.	<b>Storage</b>	Keep out of reach of children.
<b>Disposal</b>	Do not pour leftover product down the drain. Keep unwanted product in sealed containers for disposal via special chemical waste collections. Disposal of empty containers via domestic kerbside recycling programs may differ between local authorities. Check with your local council first.		

**In the case of emergency please call 1800 033 111**

### Precautions and Limitations

It is not advised to apply coatings when the temperature exceeds 35°C as they may dry too quickly under the roller, resulting in a substandard finish.

### Transport and Storage

<b>Pack A</b>	701 94907		
<b>Sizes</b>	5L	<b>Weight</b>	5.3Kg

### Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the DuSpec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the DuSpec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427

<b>Data Sheet</b>	Intergrain Enviropro 30+ Wet Edge Extender		
<b>DuSpec Data Code</b>	AUDW1436	<b>Page No</b>	2 of 2
<b>Issue No</b>	3.0	<b>Date Issued</b>	14/12/2011