

Dulux Design Chalkboard Flat

AU_DD02358

Part A	69084533
--------	----------

Description
Dulux Design Chalkboard is a water-based matt interior effect paint used as a quick convenient way of turning most surfaces into an instant chalkboard.




Features
<ul style="list-style-type: none"> Flat sheen Water based 100% Acrylic

Benefits
<ul style="list-style-type: none"> Suitable for chalkboards Same day recoat, easy clean up and low odour Provides hardwearing properties

Uses
Dulux Design Chalkboard can be applied over previously coated chalkboard surfaces as well as many other areas such as walls and doors including kitchens and children's bedrooms where a chalkboard is required. This product is not designed for use on industrially manufactured school chalkboards.

Precautions And Limitations
All preparation and painting must conform to AS2311: The Painting of Buildings. Do not use at temperatures below 10°C, or when the temperature of the surface may fall below 10°C during the drying period. Avoid exposure to steam and condensation for 48 hours after application. Although the film is dry to touch in 30 minutes, allow 7 days for film to fully cure. To care for the new chalkboard, avoid using it for at least 48 hours after painting. This will allow the chalkboard to be fully hardened and provide the best results. In humid or cool conditions allow a longer drying time of 72 hours. Use normal dusters to remove chalk, however the most effective method of removal is to lightly wash with a damp cloth or sponge.

Performance Guide			
Weather	Designed for interior use only. Not recommended for exterior use.	Heat Resistance	Resists temperatures up to 60°C.
Water	Not recommended for wet areas.	Solvent	Sensitive to aromatic hydrocarbons and alcohols.

Typical Properties			
Gloss Level	0-2 at 85 degrees	Thinner	Not recommended
Colour	Black in colour, not to be tinted	Components	1
Number Of Coats	2	Toxicity	Lead free. Dry film is non-toxic and conforms to AS 1647, Part 3.
V.O.C. Level	< 55g/L untinted	Touch Dry	30 Minutes (25°C, 50%RH)
Clean Up	 Water		
Application Method	  Brush Roller		
Application Conditions	Min	Max	Recommended
Wet Film Per Coat (microns)			
Dry Film Per Coat (microns)			
Recoat Time (min)	2 hours	Indefinite	
Theoretical Spread Rate (m ² /L)			16

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> PREVIOUSLY PAINTED SURFACES Scrape off any loose and flaking paint. Fill any imperfections with appropriate filler and sand smooth. Dust off and undercoat with one coat of Dulux 1 Step Acrylic Primer Sealer Undercoat. Previously Painted Chalkboard (not suitable for industrially manufactured school chalkboards): Sand surface. Dust off. Apply one coat of Dulux 1 Step Acrylic Primer Sealer Undercoat. UNPAINTED SURFACES Bare Paperfaced Wallboard, Cement, Brick: Brush down to remove any surface dust. Apply 1 coat of Dulux 1 Step Acrylic Sealer Primer Undercoat. Bare Interior Timber: Sand smooth. Dust off. Apply 1 coat of Dulux 1 Step Acrylic Sealer Primer Undercoat. Bare Set Plaster, Fibrous Plaster, Plasterglass: Brush down to remove any surface dust. Apply 1 coat of Dulux Sealer Binder Metal Surfaces: Thoroughly degrease and apply Dulux All Metal Primer. Repainting over Dulux Design Chalkboard - apply 1 coat of Dulux Acrylic Sealer Undercoat with a medium nap roller and allow to dry. Apply 2 coats of your chosen interior paint.
Application Procedure And Equipment	<ul style="list-style-type: none"> Stir well with a broad flat paddle using an up and down scooping action. Apply two coats of Dulux Chalkboard using a good quality brush to cut in and a short nap roller in good condition for rolling. Allow a minimum of 2 hours dry time between coats. Allow the final coat to dry and cure for at least 7 days before conditioning the chalkboard. To condition the board, rub the entire surface of the chalkboard vertically with the side of a piece of chalk, ensuring the chalkboard is completely covered. Then rub the entire surface horizontally with the side of a piece of chalk, again covering the chalkboard completely. Wipe with a soft cloth or chalkboard duster and blow off any excess chalk dust. The chalkboard is now ready to use.

Health And Safety			
MSDS Number	DLX000832		
MSDS Link	https://go.lupinsys.com/duluxgroup/harms/published_materials/fee62a9c4b8013f1e9ea398e9cc3551d-published/attachments/4ae84fdf793a11d44da2a4c61213c99d.pdf		
Health Effects	For detailed information refer to the product label and the current Material Safety Data Sheet available through Dulux Customer Service. Health Effects: No adverse effects are expected if the product is handled in accordance with the MSDS and the product label.	Protective Equipment	Personal Protective Equipment: Avoid eye contact and repeated or prolonged skin contact.
In the case of emergency, please call 1800 033 111			

Transport And Storage			
Pack A	690-84533	Shipment Name	Not dangerous goods.; No special transport requirements.
Size	500 ml; 1L	Weight	0.756kg; 1.462kg

Disclaimer
Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.
DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427